



Fire Rated 110° Multi-Core – WS52W

Application: Flexible Multi-Core Halogen free, low smoke, low toxic and corrosive emission cable for mains, submains, and the fire protection industry. Independently tested and certified to AS/NZS 3013:2005 - Category WS52W, as well as further cable manufacturing standards as outlined, and included below (see "Standards").

Norm. Operating Temp.: 110°C

Conductor: Plain annealed copper (Class 5 of IEC 60228)

Barrier: Mica Glass Tape

Insulation: X-HF-110

Sheath: HF-110-TP

Voltage: 600/1000V (0.6/1kV)

Fire Rating: WS52W

Water Rating: WS5XW

Standards: Independently tested and accredited under AS/NZS 3013:2005, and AS/NZS 5000.1:2005 by an government approved third-party independent accreditation body.

Accreditation as per "Responsible Supplier" status with the Electrical Regulatory Authorities Council (E.R.A.C.), and pertaining to manufacture as per AS/NZS 3013:2005 – WS52W, IEC 60332-3, AS/NZS IEC 60332.3.24, AS/NZS IEC60332.3.25, EN ISO 4589-3, AS/NZS IEC60754-1 (Halogen Content), AS/NZS IEC60754-2 (Low Acidity - Low Corrosion), AS/NZS IEC61034.2 (Smoke Emission), BS6387, AS/NZS 1660.5.3, AS/NZS 1660.5.4, AS/NZS 1660.5.1, AS/NZS1660.5.2, AS/NZS /NZS 5000.1, AS/NZS 3808, AS/NZS 1125, AS/NZS 3808, IEC 60332-3-24, IEC 60332-3-25, IEC 60754-1, IEC 61034-2, ISO 4589-2, general to EN50288.

Warranted: Yes



ELECTRA Part Number	SIZE	CORES	INSULATION Thickness	SHEATH Thickness	O.D.	MIN. BEND RADIUS	WEIGHT
FRC2015E	1.5	2+E	0.7 + 0.7E	1.8	12.4	250	175
FRC2025E	2.5	2+E	0.7 + 0.7E	1.8	13.5	270	224
FRC2040E	4	2+E	0.7 + 0.7E	1.8	14.2	285	261
FRC2060E	6	2+E	0.7 + 0.7E	1.8	15.1	305	310
FRC2100E	10	2+E	0.7 + 0.7E	1.8	16.8	340	410
FRC2160E	16	2+E	0.7 + 0.7E	1.8	18.8	390	560
FRC2250E	25	2+E	0.9 + 0.7E	1.8	22.5	450	790
FRC2350E	35	2+E	0.9 + 0.7E	1.8	24.6	515	1025
FRC3015E	1.5	3+E	0.7 + 0.7E	1.8	13.4	270	211
FRC3025E	2.5	3+E	0.7 + 0.7E	1.8	14.6	295	272
FRC3040E	4	3+E	0.7 + 0.7E	1.8	15.7	315	332
FRC3060E	6	3+E	0.7 + 0.7E	1.8	16.7	335	402
FRC3100E	10	3+E	0.7 + 0.7E	1.8	18.6	375	540
FRC3160E	16	3+E	0.7 + 0.7E	1.8	20.8	420	750
FRC3250E	25	3+E	0.9 + 0.7E	1.8	24.2	485	1080
FRC4015E	1.5	4+E	0.7 + 0.7E	1.8	14.5	290	246
FRC4025E	2.5	4+E	0.7 + 0.7E	1.8	15.9	320	323
FRC4040E	4	4+E	0.7 + 0.7E	1.8	17.0	340	397
FRC406E	6	4+E	0.7 + 0.7E	1.8	18.2	365	490
FRC4100E	10	4+E	0.7 + 0.7E	1.8	20.4	410	665
FRC4160E	16	4+E	0.7 + 0.7E	1.8	22.9	460	935
FRC4250E	25	4+E	0.9 + 0.7E	1.8	26.8	540	1360
FRC4350E	35	4+E	0.9 + 0.7E	1.8	29.9	600	1795
FRC2500E	50	2+E	1.0 + 0.7E	1.9	28.0	550	1350
FRC4500E	50	4+E	1.0 + 0.7E	1.9	33.8	680	2420
FRC4700E	70	4+E	1.1 + 0.9E	2.1	39.4	790	3430
FRC4950E	95	4+E	1.1 + 0.9E	2.3	43.7	875	4500

*Size = mm², O.D. ± 10%, Insulation Thickness, Sheath Thickness, O.D. & Bend Radius = mm, Weight = kg/km. Other cable combinations available.

LARGER EARTH

ELECTRA Part Number	SIZE	CORES	EARTH	INSULATION Thickness	SHEATH Thickness	O.D.	WEIGHT
XFRC4100E	10	4	10	0.7	1.8	22	695
XFRC4160E	16	4	16	0.7	1.8	24	955

*Size = mm², O.D. & Earth. ± 10%, Insulation Thickness, Sheath Thickness, & O.D. = mm. Weight = kg/km. Other cable combinations available.

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38