



Fire Rated 110° Single Core Flex – WS52W

Application: Flexible Low smoke, halogen free, low toxicity and non-corrosive emission, flame retardant cables for mains, submains, and the fire protection industry. 2 hour Fire Rating (WS52W).

Conductor: Plain Annealed Copper (Class 5 of IEC60228)

Insulation: X-HF-110

Barrier: Mica Glass Tape

Sheath: HFS-110-TP, Flame Retardant

Standards: Independently tested and accredited under AS/NZS 3013:2005, and AS/NZS 5000.1:2005 by an approved third-party independent accreditation body.

Accreditation pertains to manufacture as per AS/NZS 3013:2005 – WS52W, IEC 60332-3, AS/NZS IEC 60332.3.24, AS/NZS IEC60332.3.25, EN ISO 4589-3, AS/NZS IEC60754-1 (Halogen Content), AS/NZS IEC60754-2 (Low Acidity - Low Corrosion), AS/NZS IEC61034.2 (Smoke Emission), BS6387, AS/NZS 1660.5.3, AS/NZS 1660.5.4, AS/NZS 1660.5.1, AS/NZS 1660.5.2, AS/NZS /NZS 5000.1, AS/NZS 3808, AS/NZS 1125, AS/NZS 3808, IEC 60332-3-24, IEC 60332-3-25, IEC 60754-1, IEC 61034-2, ISO 4589-2, general to EN50288.

Greenstar Certified: Yes
(Pathway 2 - as per the Green Building Council of Australia)

V.C.A. Endorsed: Yes
(Vinyl Council of Australia)

Warranted: Yes

ELECTRA Part Number	SIZE	INSULATION Thickness	SHEATH Thickness	O.D.	MIN. BEND RADIUS	WEIGHT
FRF1100**	10	0.7	1.4	9.4	190	160.0
FRF1160**	16	0.7	1.4	10.5	210	225.0
FRF1250**	25	0.7	1.4	12.2	245	320.0
FRF1350**	35	0.9	1.4	13.5	270	425.0
FRF1500**	50	0.9	1.4	15.2	305	575.0
FRF1700**	70	1.0	1.5	17.5	350	790.0
FRF1950**	95	1.1	1.6	19.4	390	1015.0
FRF11200**	120	1.2	1.6	21.2	425	1270.0
FRF11500**	150	1.3	1.7	23.6	470	1575.0
FRF11850**	185	1.6	1.8	25.9	520	1905.0
FRF12400**	240	1.7	1.9	29.1	580	2475.0
FRF13000**	300	1.8	2.0	31.9	640	3050.0
FRF14000**	400	2.0	2.1	35.7	715	3900.0
FRF15000**	500	2.2	2.3	39.7	795	5025.0
FRF16300**	630	2.4	2.4	43.0	900	6590.0

*Size = mm², O.D. ± 10%, Insulation Thickness, Sheath Thickness, O.D. & Bend Radius = mm, Weight = kg/km

** Please place "GY" here (Part Number) to indicate Earth (Green / Yellow).

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38