



Fire Rated Data Cable – Overall Screened

Application: Internal and External Interconnections of electronic apparatus such as computers, intercoms, telemetering, signalling, and alarms systems.

Conductor: Plain Annealed Copper Wire

Voltage: 450/750V

Barrier: Mica Glass Tape (WS52W)

Insulation: X-HF-110

Screen: Aluminium tape screen, polyester mylar tape lapping and, 7/0.25mm copper drain wire.

Sheath: HFS-110-TP

Sheath Colour: Red

Core Colours: White and Black numbered cores.

Standards: AS/NZS 3013:2005, AS/NZS 3191, AS/NZS 1125

Pack Lengths: 100m, 250m, and 500m

NOT TO BE CONNECTED TO MAINS

ELECTRA Part Number	SIZE	PAIRS & CORES	VOLTAGE Max. (RMS)	O.D.
FREAS73202	0.6	2 Cores	300	
FREAS7401P	0.88	1 Pair	300	7.9
FREAS7501P	1.5	1 Pair	300	8.4

**Size = mm², O.D. ± 10%.*

Fire Rated Variable Speed Drive Cables - VSD

Application: Supply motors from variable speed controllers in fixed installations. Designed to significantly reduce radiated interference from electrical noise.

Conductor: Plain Annealed Copper Wire (Class 5)

Voltage: 600/1000V (0.6/1kV)

Barrier: Mica Glass Tape (WS52W)

Insulation: X-HF-110

Screen: Tinned Copper Wire - Braided

Sheath: HFS-110-TP

Sheath Colour: Red

Core Colours: (3C+E) Red, White, Blue, Green/Yellow

Standards: AS/NZS 3013:2005, AS/NZS 5000.1, AS/NZS 1125

ELECTRA Part Number	SIZE	CORES	INSULATION Thickness	SHEATH Thickness	O.D.
FRVSD3015E	1.5	3C+E	0.7	1.8	14.3
FRVSD3025E	2.5	3C+E	0.7	1.8	15.0
FRVSD3040E	4	3C+E	0.7	1.8	16.3
FRVSD3060E	6	3C+E	0.7	1.8	17.5
FRVSD3100E	10	3C+E	0.7	1.8	19.7
FRVSD3160E	16	3C+E	0.7	1.8	22.3

**Size = mm², O.D. ± 10%, Insulation Thickness, Sheath Thickness and O.D. = mm*

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38