



# Flat TPS Cables

**Application:** Easy-peel sheath for general wiring. This cable is used for residential and light commercial construction. Installation is usual where the installation is not subject to mechanical damage.

**Conductor:** Plain Annealed Copper

**Insulation:** PVC V-90

**Sheath:** 3V-90 Easytear

**Voltage:** 450/750V

**Standards:** AS/NZS 5000.2, AS/NZS 1125, AS/NZS 3808

**Greenstar:** Approved

**Drum Sizes:** 100m, 300m, 500m

## Twin and Earth (2C+E)

ELECTRA Part Number	SIZE	CORES	INSULATION Thickness	SHEATH Thickness	SHEATH Colours Available	O.D.
SRF3010V	1.0	2C+E	0.6	0.9	White	9.0 x 4.2
SRF3015V	1.5	2C+E	0.6	0.9	White / Black / Grey / Red Trace	10.0 x 4.6
SRF3025V	2.5	2C+E	0.7	1.0	White / Black / Grey / Red-Trace	12.4 x 5.5
SRF3040V	4	2C+E	0.8	1.1	White / Black / Grey	14.0 x 6.5
SRF3060V	6	2C+E	0.8	1.1	White / Black / Grey	15.2 x 7.1
SRF3100V	10	2C+E	1.0	1.2	White	18.9 x 8.6
SRF3160V	16	2C+E	1.0	1.3	White	21.8 x 9.9

*\*Size = mm<sup>2</sup>, O.D. ± 10%, Insulation Thickness, Sheath Thickness & O.D. = mm. Also see LSZH, AC, HT, Non-Migratory variations.*

## 3C+E Flat

ELECTRA Part Number	SIZE	CORES	INSULATION Thickness	SHEATH Thickness	SHEATH Colours available	O.D.
SRF4015V	1.5	3C+E	0.6	0.9	White	12.6 x 4.6
SRF4025V	2.5	3C+E	0.7	1.0	White	15.8 x 5.5

*\*Size = mm<sup>2</sup>, O.D. ± 10%, Insulation Thickness, Sheath Thickness & O.D. = mm.*

## Twin and Twin Active

ELECTRA Part Number	SIZE	CORES	INSULATION Thickness	SHEATH Thickness	SHEATH Colours Available	O.D.
SRF2010V	1	Red / Black	0.6	0.9	White	6.5 x 4.2
SRF2010AV	1	Red / White	0.6	0.9	White	6.5 x 4.2
SRF2015V	1.5	Red / Black	0.6	0.9	White	7.2 x 4.6
SRF2015AV	1.5	Red / White	0.6	0.9	White / Black	7.2 x 4.6
SRF2025V	2.5	Red / Black	0.7	1.0	White / Black	8.9 x 5.5
SRF2025AV	2.5	Red / White	0.7	1.0	White	8.9 x 5.5
SRF2040V	4	Red / Black	0.8	1.1	White / Black	10.6 x 6.5
SRF2040AV	4	Red / White	0.8	1.1	White	10.6 x 6.5
SRF2060V	6	Red / Black	0.8	1.1	White	11.7 x 7.1
XSRF2060V**	6	Red / Black	0.8	1.1	Orange	11.7 x 7.1
SRF2060AV	6	Red / White	0.8	1.1	White	11.7 x 7.1
SRF2100V	10	Red / Black	1.0	1.2	White	14.6 x 8.6
XSRF2100V**	10	Red / Black	1.0	1.2	Orange	14.6 x 8.6
SRF2160V	16	Red / Black	1.0	1.3	White	16.9 x 9.9
XSRF2160V**	16	Red / Black	1.0	1.3	Orange	16.9 x 9.9

*\*Size = mm<sup>2</sup>, O.D. ± 10%, Insulation Thickness, Sheath Thickness & O.D. = mm. \*\*Available in WA only*

[electracables.com.au](http://electracables.com.au)

**SYDNEY**  
**(02) 8786 5200**

**MELBOURNE**  
**(03) 9706 6819**

**BRISBANE**  
**(07) 3386 9800**

**PERTH**  
**(08) 9454 2628**

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38