


access floor service outlet boxes

empty boxes



slab and screed mounted floor boxes

empty boxes



Selection charts **p. 26**
Dimensions and technical information **p. 31**

Lid and trim mouldings are precision engineered from hard wearing durable ABS. Lid is reinforced with a galvanised mild steel plate
Mounting frame and box base - 0.9 mm thick galvanised steel
Each compartment has 2 entries for 20 mm and 2 entries for 25 mm flexible conduits
Grey mouldings. Alternative colours available to special order
Grey plates
2, 3 and 4 compartment boxes are also available with separate individual compartment base units for convenient offsite pre-wiring
Supplied in parts or fully assembled and configured to customer specification
Conform to IEC-61534-22

Selection charts **p. 26**
Dimensions and technical information **p. 31**

Electrak slab floor boxes are an ideal solution for underfloor power and data requirements
Used in conjunction with Electrak floor grommets, slab boxes prevent unwanted access to power and data connections

Pack	Cat. Nos.	2 compartment floor boxes
		Empty boxes
		100 mm compartment widths
1	CR2001	Single base - 75 mm depth
1	CR2002	Single base - 85 mm depth (standard box)
1	CR2003	Single base - 110 mm depth
1	CR2004	Separate compartment base - 75 mm depth
1	CR2005	Separate compartment base - 85 mm depth
1	CR2006	Separate compartment base - 110 mm depth

		3 compartment floor boxes
		Empty boxes
		100 mm compartment widths
1	CR011	Single base - 75 mm depth
1	CR012	Single base - 85 mm depth (standard box)
1	CR013	Single base - 110 mm depth
1	CR014	Separate compartment base - 75 mm depth
1	CR015	Separate compartment base - 85 mm depth
1	CR016	Separate compartment base - 110 mm depth

		4 compartment floor boxes
		Empty boxes
		75 mm compartment widths
1	CR4001	Single base - 75 mm depth
1	CR4002	Single base - 85 mm depth (standard box)
1	CR4003	Single base - 110 mm depth
1	CR4004	Separate compartment base - 75 mm depth
1	CR4005	Separate compartment base - 85 mm depth
1	CR4006	Separate compartment base - 110 mm depth

Pack	Cat. Nos.	Slab floor boxes
		Fixes directly onto floor slab Fast and efficient installation with integrated fixing plates Wide range of power and data accessory plates Manufactured from 0.9 mm thick galvanised steel Each compartment has 2 entries for 20 mm and 2 entries for 25 mm flexible conduits
		100 mm compartment widths
		Use plates from the 1, 2 and 3 compartment floor box section p. 26
1	CR5102	1 compartment slab floor box
1	CR5202	2 compartment slab floor box
1	CR5302	3 compartment slab floor box
		75 mm compartment widths
		Use plates from the 4 compartment floor box section p. 26
1	CR5402	4 compartment slab floor box
		Screed floor boxes
		25 mm conduit fed, to suit screed 75 mm to 90 mm deep
1	CR5312	3 compartment screed floor box
1	CR5412	4 compartment screed floor box

Edge trim boxes, and metal or lockable lids are available to order
contact us on +44 (0) 345 600 6266

