

Product Data Sheet



ELECTRAK

Intersoc-R Pre-Wired Interconnection Intersoc to Intersoc 16A 1m

REF. IAB610A | EAN. 5012774498261

> [Link to e-catalog product sheet](#)

Technical characteristics

Connection 1	Other
Connection 2	Other
Connector system system-oriented	Yes
Number of cores	3
Nominal cross section conductor	1.5 mm ²
Length	1 m
Material outer sheath	Polyvinyl chloride (PVC)
Temperature resistance	0-90 °C
Nominal current	16 A
Nominal voltage	250-250 V
Frequency	50-60 Hz

Colour outer sheath	Black
Spiralized cable	No
With protective conductor	Yes
Degree of protection (IP)	Other
Oil resistant according to EN IEC 60811-404	No
With cord switch	No
Outer diameter approx.	8.9 mm
Reaction-to-fire according to EN 13501-6: Class	None
Reaction-to-fire according to EN 13501-6: Smoke production	None
Reaction-to-fire according to EN 13501-6: Flaming droplets/particles	None
Reaction-to-fire according to EN 13501-6: Acidity	None

Documents

Catalogue pages

[powering-the-workplace-2023-043.pdf](#) | PDF (0.27Mo)

Agreements & certificates

[LGRP-00995-V01.01-EN.pdf](#) | PDF (0.61Mo)