Technical Specification

Product Code: 72212

Description: Standard 2 Module 2 Channel, 7 Day, 46 Operations



General Information

Dimensions	90mm x 36mm x 63mm
Display	LCD Display
Wire Gauge	0.5 - 2.5mm²
Time Base	Quartz Crystal
Quartz Crystal Accuracy (at 20°C)	≤ ± 0.5 Seconds/Day

Power

Operating Voltage	230VAC
Power Consumption	0.2 ~ 1W
Power Reserve @ 20°C	Approx. 10 Years
Battery Type	Replaceable CR2032
IEC Protection Class	Class II when installed according to regulations

Construction

Material	Self-Extinguishing Thermoplastic
Fixing	Surface Mounting or DIN
Distribution Board Mounting	35mm DIN-rail (DIN EN 60715)
Module Size	2

Outputs

Contact Type	2 x SPDT
Total Switch Rating	16A @ 1.0pf, 230VAC
Min Switching power	500 mW (10V/10mA)
Maximum Current Rating	Max Starting Current 30A
Halogen, Filament Lamp	1000W
Fluorescent Lamp with electron. lamp ballast	500W
Fluorescent Lamp with convent. lamp ballast	400W
Compact Fluorescent Lamp	300W
LED 230VAC	300W

Programming

Programming Schedule	24 Hour, and 7 Day Programmable
Available Operations	46 Operations
Switching Modes	ON, OFF, Pulse
Summer/Winter Time Change	Yes; Automatic
Pulse length - Pulse function (switching time)	00:01 up to 59.59 mm:ss
Pulse length - Timer (man. switching)	0:00:01 up to 9:59:59 h:mm:ss

Environment

Ingress Protection	IP20 (DIN EN 60529)
Operating Temperature	-30°C to 55°C

Accessories

143602	Module Enclosure
25195	Easy Vue Hub Programming Interface
25196	Easy Vue Hub Programming Interface with Bluetooth
25193	Programming Interface

Features

- Volt-free 16A changeover contact
- 46 memory locations
- Module timer
- Simple programming
- Works with key programming & EasyVUE (Key & hub are optional extras)
- Battery Reserve: 10 years

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com

BACKLIT DISPLAY | 300W LED | 3 YEAR GUARANTEE

Errors & Omissions excluded.
Specification is subject to change without notice.