

**Product Code:** APDSMW

**Description:** MultiWay Video Door Station



### General Information

<b>Dimensions</b>	200mm x 87mm x 53mm
<b>Sensor Size</b>	1/3"
<b>Lens size</b>	3.6mm
<b>Viewing Angle</b>	70 Degrees
<b>Audio</b>	Full Duplex
<b>Illumination</b>	5 White light LEDs
<b>Sensitivity</b>	0.1 Lux
<b>User Interaction</b>	0 - 9, * and #
<b>Maximum Call-able address</b>	32
<b>Code lengths</b>	2 - 6
<b>Maximum Access Codes</b>	32 PINs
<b>Recommended BUS Cable</b>	Cat5e or higher
<b>Weight</b>	640g

### Outputs

<b>Lock outputs</b>	2
<b>Global selections</b>	Normally Open or Normally Closed; Volt-Free or 12VDC300mA

### Transmission

<b>Protocol</b>	BUS
<b>Effective Distance to PSU</b>	50m

### Environment

<b>Ingress Protection</b>	IP55
<b>Operating Temperature</b>	-20°C to 40°C

### Power

<b>Operating Voltage</b>	24VDC BUS
--------------------------	-----------

### Construction

<b>Material</b>	Aluminium Alloy
<b>Fixing</b>	Surface & Flush (requires APDSKPFMS) Mounted

### Accessories

<b>EVBPSBB</b>	12V Lock power supply with battery backup
<b>APPOWMW</b>	Aperta Multiway power supply
<b>APSEPMW</b>	Aperta Multiway BUS Separator
<b>APMONW, APMONB, APMONWG, APMONBG, APAUDH, APAUDHBLK</b>	Compatible Aperta Monitors
<b>ENTERD</b>	Flush Electric Lock
<b>ENTERD-YLR</b>	Surface Electric Lock

### Component Supplied

Fixing Screws, and Wall Plugs  
User Manual

### Additional Information

Simple 2-core Installation  
High-Resolution Colour Camera  
Can call addresses 1 ~ 32