



General Information

Dimensions	165mm x 85mm x 53mm
Sensor Size	1/3"
Lens size	3.6mm
Audio	Full Duplex
Illumination	5 White light LEDs
Sensitivity	0.1 Lux
Recommended BUS Cable	Cat5e or higher
Weight	390g

Power

Operating Voltage	24VDC BUS
-------------------	-----------

Construction

Material	ABS
Fixing	Surface Mounting

Outputs

Lock outputs	2
Global selections	Normally Open or Normally Closed; Volt-Free or 12VDC300mA

Transmission

Protocol	BUS
Effective Distance to PSU	50m

Environment

Ingress Protection	IP55
Operating Temperature	-20°C to 40°C

Accessories

EVBPBB	12V Lock power supply with battery backup
APPOWSWDR	Din Mounted BUS power supply
APMONW	Aperta BUS Monitor in white
APMONB	Aperta BUS Monitor in Black
APMONWG	Aperta GUI BUS Monitor in white
APMONBG	Aperta GUI BUS Monitor in Black
APAUDH	Aperta BUS Audio Only Handset in White
APAUDHBLK	Aperta BUS Audio Only Handset in Black
ENTERD	Flush Electric Lock
ENTERD-YLR	Surface Electric Lock

Component Supplied

Fixing Screws, and Wall Plugs
User Manual

Additional Information

Simple 2-core Installation
High-Resolution Colour Camera