

Product Code: APKITKPLK

Description: Colour Video Door Entry System with Keypad



Part 1: APMONB

General Information

Sensor Size	1/3"
Lens size	3.6mm
Audio	Full Duplex
Illumination	5 White light LEDs
Sensitivity	0.1 Lux
User Interaction	0 - 9, *, #, and Bell
Code lengths	2 - 6
Weight	640g

Transmission

Protocol BUS

Effective Distance to PSU 50m

Construction

Material	Aluminium Alloy
Fixing	Surface & Flush (requires APDSKPFMS)
	Mounted

Outputs

Lock outputs	2
Global selections	Normally Open or Normally Closed; Volt-Free or 12VDC300mA

Power

Operating Voltage 24VDC BUS

Environment

Ingress Protection	IP55
Operating Temperature	-20°C to 40°C

Accessories

EVBPSBB	12V Lock power supply with battery backup
APPOWSWDR	Din Mounted BUS power supply
APMONW	Aperta BUS Monitor in white
APMONB	Aperta BUS Monitor in Black
APMONWG	Aperta GUI BUS Monitor in white
APMONBG	Aperta GUI BUS Monitor in Black
APAUDH	Aperta BUS Audio Only Handset in White
APAUDHBLK	Aperta BUS Audio Only Handset in Black
ENTERD	Flush Electric Lock

Additional Information

- Simple 2-core Installation
- High-Resolution Colour Camera

Part 2: APDSSWKP

Operating Voltage	24VDC BUS
Consumption	300mA
Effective Distance to PSU	100m
Construction	ABS
Indication	LED and Audio
Operating Temperature	0°C to 40°C
Ingress Protection	IP20
Dimensions	152mm x 215mm x 18mm
Weight	450g
Colour	Black
Fixing	Surface Mounting



Part 3: APPOWSWDR

Operating Voltage	110-220VAC
Construction	ABS
Indication	LED
Short Protection	PTC-Fuse
Ingress Protection	IP20
Fixing	Surface Mounting, and DIN Rail
Dimensions	60mm x 90mm x 105mm
Weight	450g
Colour	White
Output	24VDC BUS @ 800mA

Component Supplied

- Fixing Screws, and Wall Plugs
- User Manual