MAGfire®

# Technical Specification

**Product Code:** **MAGPRO-CPIP67**

**Description:** Addressable IP67 Rated Red Manual Call Point



## General Information

| | |
|---|---|
| Dimensions | 114mm x 114mm x 80mm |
| Protocol Type | Custom (Closed) |
| Type of the frangible element | A |
| Wire Gauge | 0.4 - 2.0 mm |
| Weight | 262g |

## Power

| | |
|---|---|
| Operating Voltage | 15 - 32 VDC |
| Consumption Without Communication | 125μA @ 27VDC |
| Consumption With Communication | 160μA @ 27VDC |
| Consumption in Fire Mode | 3 mA |

## Environment

| | |
|---|---|
| Ingress Protection | IP67 |
| Relative Humidity Resistance | (93 ± 3)% @ 40°C |
| Operating Temperature | -10°C to 60°C |

## Accessories

| | |
|---|---|
| MAGPRO-CPC | Pack of 5 Callpoint Covers |
| MAGPRO-PROG | Address Programming Tool For MAGPRO Devices |

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
**T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143
**E**: info@espuk.com | **W:** espuk.com

CPR COMPLIANT EN54 CE


Errors & Omissions excluded.
Specification is subject to change without notice.