

**Product Code:** MAGPRO96

**Description:** Addressable 96 Zone Fire Panel



### General Information

<b>Dimensions (Metal Casing)</b>	441mm x 331mm x 80mm
<b>Dimensions (Front Cover)</b>	461mm x 344mm x 45mm
<b>Protocol Type</b>	Custom (Closed)
<b>Zones</b>	16 Per Loop
<b>Loops</b>	Up To 4
<b>Maximum Number of events in Log</b>	10240
<b>Wire Gauge</b>	Up to 1.5mm
<b>Weight</b>	6Kg
<b>Warranty</b>	3 Years

### Environment

**Operating Temperature** -5°C to 50°C

### Power

<b>Operating Voltage</b>	230 VAC ± 10% 50/60Hz
<b>PSU Output</b>	7A
<b>Standby Supply</b>	Up to 12V 17Ah (Battery Calculation Required)

### Outputs

<b>Monitored Outputs</b>	4
<b>Dimensions (Front Cover)</b>	461mm x 344mm x 45mm
<b>Un-Monitored Outputs</b>	4 (240VAC @ 10A)
<b>Auxiliary Output</b>	24VDC @ 300mA

### Inputs

<b>Max Devices per Loop</b>	Up to 250 Devices (Loop Calculation Required)
<b>Maximum number of Loops</b>	Expandable up to 2

### Accessories

<b>MAGDUOPK</b>	Pack of 2 Keys
<b>MAGBAR2/4</b>	Key & Barrel set

2 x 10k Ohm Resistors, 1 x 2A Quick-Blow Fuse

### Additional Features

Integral sound alarm button  
Enable/disable security key  
One man walk test facility  
Individual sounder circuit fault ID  
Individual zone/sounder isolate  
Class change' facility