

Product Code: PA16922

Description: Standard Analogue 7 Day Timer



General Information

Full Dimensions 72mm x 94.5mm x 53mm

Display Mechanical Dial

Connection by cage terminals, section of conductors 1 - 6 mm²

Time Base Quartz Crystal

Accuracy of Operation 1 sec / 24 Hour

Power

Operating Voltage 230VAC

Power Consumption 0.5A~

IEC Protection Class Class II when installed according to regulations

Construction

Material Self-Extinguishing Thermoplastic

Fixing Surface, Panel, or DIN

Distribution Board Mounting 35mm DIN-rail (DIN EN 60715)

Outputs

Contact Type SPDT

Panel Dimensions 72mm x 72mm

Total Switch Rating 16A (3) A

Resistive Load 16A 250V

Voltage Free Inductive Load (cos = 0.6) 3A 250V

Incandescent Lamps 1000W 250V

Squirrel-Cage Motor 350W 250V

Programming

Programming Schedule 24 Hour, and 7 Day Programmable

Available Operations 84 Operations

Switching Modes ON and OFF

Switching Accuracy 10 Minutes

Environment

Ingress Protection IP20 (DIN EN 60529)

Storage Temperature -20°C to +60°C

Operating Temperature -10°C to 50°C

Accessories

95587 Panel Converting Mounting Kit

Features

- Voltage free 16A changeover contact
- Suitable for Surface, Panel or Din rail mounting
- Programming by 1 hour captive segments
- Manual override with automatic return to program
- Contact status display
- Voltage free 16A changeover contact
- Suitable for Surface, Panel or Din rail mounting
- Programming by 1 hour captive segments
- Manual override with automatic return to program
- Contact status display