Technical Specification

Product Code: Q553.13.12

Description: Astro Zone 2, 4 Pin Time Switch, 1 On/Off & optional early off



General Information

Dimensions	146.5mm x 105.7mm x 82mm
Display	24 Hour Dial
Wire Gauge	0.5 - 4mm²
Time Base	Quartz Crystal
Timing Accuracy	5 Minutes/Year

Power

Operating Voltage	230VAC
Power Consumption	0.6W @ 230V
Power Reserve	20 Days
IEC Protection Class	Class I (Must be earthed)
Live Parts Protection	Contained within the enclosure

Construction

Base Type	4 Pin
Fixing	Surface Mounting

Outputs

Contact Type	SPST
Total Switch Rating	20A, 230VAC
Maximum Current Rating (0.6pf Inductive)	5A
Maximum Current Rating (0.8pf Inductive)	12A
Halogen, Filament Lamp	3600W
Discharge (Sodium, Mercury, Metal Halide)	3600W
Fluorescent Lamp	1980W
LED 230VAC	3600W

Programming

Programming Schedule	24 Hour Program
Day Omission	No
Temporary Override Facility (Manual Button)	Advance to “OFF”, when program “ON” and will remain “OFF” unit next “ON” operation and vice versa
Dial Calibration	Zone 2
Setting Accuracy	+/- 3 Minutes
Available Operations	1 ON/OFF Period
Sunrise/Sunset Time Offset	(+/-) 45 Minutes
Early “Off” on selected day	

Environment

Ingress Protection	IP20
Operating Temperature	0°C to 50°C

Accessories

110469 FD930 Conduit Box Time Switch

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com

3600W LED

5 YEAR GUARANTEE

Errors & Omissions excluded.
Specification is subject to change without notice.