



Multi-Fixing Exit Sign

LED Multi Fixing Exit Sign

DESCRIPTION

Versatile fitting offering 4 different fixing options for maximum flexibility and long term performance

FEATURES

- Polycarbonate construction
- Comes complete with 4 fixing options – Ceiling mounted, end mounted, wall mounted and suspended (adjustable length 1m suspension cable included). Additional recessed option available with EXITREC
- Supplied with a double-sided up arrow ISO format exit legend – Full range of alternative legend directional panels available separately including signs directive format
- 3 hour maintained mode as standard which can also be configured for non-maintained or remote switched operation
- Viewing distance 30m
- LED charge light and battery test button
- Battery – LiFePO4 3.2V 1500mAh. Battery 5 year warranty – Replacement battery code: EB35

GENERAL INFORMATION

Light Source	LED	Colour / Finish	White
Application	Internal	Mounting Type	Surface, Recessed, Suspended
Product Warranty	5 Years	Battery Warranty	5 Years
Net Weight	1.13 kg		

TECHNICAL INFORMATION

Nominal Voltage	240	Frequency	50Hz
Class Protection	1	Operating Temperature (Min)	0 °C
Operating Temperature (Max)	40 °C	Construction Materials Line 1	Polycarbonate
IP Rating	IP20		

PRODUCT INFORMATION

Wattage Combined	2.8W	CCT Combined	6000K
Luminaire Lumens Combined	38 lm	lm/W Combined	14 lm/w
Beam Angle	120°	CRI	70
Emergency Lumen Output	38 lm	Dimmable	Not Dimmable
Displacement Factor	0.26		



PHOTOMETRICS

Product Code	Product Type	Watts	CCT	Luminaire lumens	Lm/W
EXITMMO	Emergency	2.8 W	6000 K	38 lm	14 lm/W

ACCESSORIES

Product Code	Description	MOM / OPQ
EB8	Ni-Cd 3.6V 800mAh Side-by-side Battery	1 / 1
EMMOD	Signs Directive Down Legend for EXITMMO	1 / 100
EMMOLR	Signs Directive Left/Right Legend for EXITMMO	1 / 100
EMMOUP	Signs Directive Up Legend for EXITMMO	1 / 100
EXITREC	Recessed Mounting Kit for EXITMMO	1 / 25
ISOMMOD	ISO Down Arrow Legend for EXITMMO	1 / 100
ISOMMOLR	ISO Left/Right Arrow Legend for EXITMMO	1 / 100

PACKAGING

Packaging Type	Colour Box
Individual unit gross weight	1,180 g
Pallet Layer Qty	36
Pallet Layers	3
Pallet Qty	108
MOM / OPQ	1 / 6

