


Eterna

HL60 Range



This luminaire is compatible with bulbs of the energy classes:



874/2012



LAMP REPLACEMENT:

Switch off the electricity at the mains.

Undo the screws at the top and bottom of the fitting and lift off the front.

Remove and replace lamp.

Replace the front of the fitting and tighten the two screws.

REPLACEMENT LAMP TYPE:

Requires 1 x suitable ES energy saving lamp (not included).

Fitting is rated at 60W max.

CLEANING:

Clean this light fitting only with a soft dry cloth.

Do not use any chemical or abrasive cleaners.

EVENTUALLY, YOU MAY WANT TO REPLACE THIS PRODUCT:

Regulations require the recycling of Waste from Electrical and Electronic Equipment (European "WEEE Directive" effective August 2005—UK WEEE Regulations effective 2nd January 2007). Environment Agency Registered Producer: WEE/GA0248QZ.

WHEN YOUR PRODUCT COMES TO THE END OF ITS LIFE OR YOU CHOOSE TO REPLACE IT, PLEASE RECYCLE IT WHERE FACILITIES EXIST - DO NOT DISPOSE WITH HOUSEHOLD WASTE.



IF YOU EXPERIENCE PROBLEMS:

If you believe your product is defective, please return it to the place where you bought it. Our Technical Team will gladly advise on any Eterna Lighting product, but may not be able to give specific instructions regarding individual installations.



INSTALLATION INSTRUCTIONS

A guide for qualified electricians



Pack contents:

- Half lantern
- Mounting fixtures

Model: HL60B / HL60WH Half Lantern

These instructions are provided as a guideline to assist you.

**PLEASE READ THESE INSTRUCTIONS BEFORE INSTALLATION
AND RETAIN FOR FUTURE REFERENCE**

Issue 2013



FOR PRODUCT ADVICE:

- T: 01933 673 144
- F: 01933 678 083
- E: sales@eterna-lighting.co.uk

Visit our website:

www.eterna-lighting.co.uk

READ THIS FIRST:

Check the pack and make sure you have all of the parts listed on the front of this booklet. If not, contact the outlet where you bought this product.

This product must be installed by a competent person in accordance with the current building and IEE wiring regulations.

As the buyer, installer and/or user of this product it is your own responsibility to ensure that this fitting is fit for the purpose for which you have intended it. Eterna Lighting cannot accept any liability for loss, damage or premature failure resulting from inappropriate use.

This product is designed and constructed according to the principles of the appropriate British Standard and is intended for normal domestic service.

The lifetime of compact fluorescent lamps and ballasts are negatively affected by increased switching i.e. where a PIR is being used to control the fitting.

This light fitting must be installed in accordance with the Building Regulations. These may be obtained from HMSO or viewed and downloaded from www.communities.gov.uk following the link for Building Regulations.

Switch off the mains before commencing installation and remove the appropriate circuit fuse.

Suitable for outdoor use.

This product is suitable for installation on surfaces with normal flammability, e.g. wood, plasterboard, masonry. It is not suitable for use on highly flammable surfaces (e.g. polystyrene, textiles).

Before making fixing hole(s), check that there are no obstructions hidden beneath the mounting surface such as pipes or cables.

The chosen location of your new fitting should allow for the product to be securely mounted and safely connected to the mains supply (lighting circuit).

If the location of your new fitting requires the provision of a new electrical supply, the supply must conform with the requirements of the Building Regulations.

This product is designed for permanent connection to fixed wiring: this should be either a suitable lighting circuit (protected with a 5 or 6 Amp MCB or fuse) or a fused spur (with a 3 Amp fuse) via a fused connection unit. We recommend that the supply incorporates a switch for ease of operation.

Make connections to the electrical supply in accordance with the following code:

Live - Brown or Red
Neutral - Blue or Black

This fitting is double insulated, do not connect any part to earth.

You are advised at every stage of your installation to double-check any electrical connections you have made. After you have completed your installation there are electrical tests that should be carried out: these tests are specified in the Wiring Regulations (BS7671) referred to in the Building Regulations.

INSTALLATION:

- 01) Undo the screws at the top and bottom of the fitting and lift off the front.
- 02) Undo the screw in the plastic cover at the bottom of the lampholder and prize off the cover.
- 03) Using the back of the fitting as a template, mark the location of the fixing holes.
- 04) Pierce the rubber grommet in the back of the fitting. Make the hole as small as possible so that a good watertight seal is maintained when the cable has been threaded through.
- 05) Thread the cable through the grommet.
- 06) Secure the fitting to the wall using fixings (supplied). If the fixings supplied with your fitting are not appropriate to your installation, select suitable alternatives.
- 07) Make the connections to the lampholder according to the colour code.
- 08) Replace the cover on the bottom of the lampholder and tighten the screw.
- 09) Insert suitable ES energy saving lamp.
- 10) Replace the front of the fitting and tighten the screws.
- 11) Restore the power and switch on.