



LED Emergency Exit Drop Sign


LED Emergency Hanging Exit Sign Light

DESCRIPTION

Fitting with proven long term durability and performance – perfect for office & commercial applications

FEATURES

- Remote connection box complete with adjustable length suspension cable (max 80cm)
- Supplied with a double-sided exit legend
- 3 hour maintained mode as standard which can also be configured for non-maintained or remote switched operation
- Viewing distance 29m
- Test button and LED charge light



GENERAL INFORMATION

|                  |          |                  |           |
|------------------|----------|------------------|-----------|
| Light Source     | LED      | Colour / Finish  | White     |
| Application      | Internal | Mounting Type    | Suspended |
| Product Warranty | 5 Years  | Battery Warranty | 5 Years   |
| Net Weight       | 0.75 kg  |                  |           |

TECHNICAL INFORMATION

|                               |               |                               |               |
|-------------------------------|---------------|-------------------------------|---------------|
| Nominal Voltage               | 240           | Frequency                     | 50Hz          |
| Class Protection              | I             | Operating Temperature (Min)   | 0 °C          |
| Operating Temperature (Max)   | 40 °C         | Average Rated Life            | 25,000 h      |
| Construction Materials Line 1 | Polycarbonate | Construction Materials Line 2 | Acrylic Panel |
| Dimensions - Height           | 227 mm        | Dimensions - Width            | 340 mm        |
| Dimensions - Depth            | 45 mm         | IP Rating                     | IP20          |

PRODUCT INFORMATION

|                           |        |               |              |
|---------------------------|--------|---------------|--------------|
| Wattage Combined          | 3W     | CCT Combined  | 6000K        |
| Luminaire Lumens Combined | 170 lm | lm/W Combined | 57 lm/w      |
| Emergency Lumen Output    | 35 lm  | Dimmable      | Not Dimmable |
| Displacement Factor       | 0.26   |               |              |



## PHOTOMETRICS

| Product Code | Product Type | Watts | CCT    | Luminaire lumens | Lm/W    |
|--------------|--------------|-------|--------|------------------|---------|
| SESIGNLEM3   | Emergency    | 2.3 W | 6000 K | 170 lm           | 74 lm/W |
| SIGNLEDEM3   | Emergency    | 3 W   | 6000 K | 170 lm           | 57 lm/W |

## ACCESSORIES

| Product Code | Description                                          | MOM / OPQ |
|--------------|------------------------------------------------------|-----------|
| EB8          | Ni-Cd 3.6V 800mAh Side-by-side Battery               | 1 / 1     |
| ISOSIGND     | ISO Down Arrow Legend for SIGNLEDEM3 /<br>SESIGNLEM3 | 1 / 100   |
| ISOSIGNLR    | ISO Left/Right Legend for SIGNLEDEM3 /<br>SESIGNLEM3 | 1 / 100   |
| SIGNLGD      | Left/Right Legend for SIGNLEDEM3                     | 1 / 100   |
| SIGNLGDUP    | Up Arrow Legend for SIGNLEDEM3                       | 1 / 100   |

## PACKAGING

|                              |           |
|------------------------------|-----------|
| Packaging Type               | Plain Box |
| Individual unit gross weight | 754 g     |
| Pallet Layer Qty             | 36        |
| Pallet Layers                | 4         |
| Pallet Qty                   | 144       |
| MOM / OPQ                    | 1 / 6     |

