


FLEXIBLE DUCT (NON-INSULATED)



- Suitable for general exhaust and supply air applications such as bathrooms, ensuites and toilets.
- Fibre woven metallic duct provides durability and tear resistance.
- High tensile wire sprung to retain duct shape and flexibility.
- Complies with Australian/New Zealand Standards: Construction contains high grade flame retardant with a 3 zero fire rating - AS/NZS 4254.

PART NO.	DUCT DIAMETER, MM	DUCT LENGTH, M	TRADE PACK CONTENTS
DUCT100-6M	100	6	-
DUCT100-6M-TP	100	6	10 lengths
DUCT125-6M	125	6	-
DUCT125-6M-TP	125	6	10 lengths
DUCT150-6M	150	6	-
DUCT150-6M-TP	150	6	10 lengths
DUCT200-6M	200	6	-
DUCT250-6M	250	6	-
DUCT300-6M	300	6	-

Note: Trade pack duct comes loose in box

FLEXIBLE DUCT (INSULATED)



- Thermally insulated outer sleeve to minimise heat gain or heat loss.
- Fibre woven metallic inner duct provides durability and tear resistance.
- High tensile wire sprung to retain duct shape and flexibility.
- Complies with Australian/New Zealand Standards: Construction contains high grade flame retardant with a 3 zero fire rating - AS/NZS 4254.

PART NO.	DUCT DIAMETER, MM	DUCT LENGTH, M
DUCT150INS-6M	150	6
DUCT200INS-6M	200	6
DUCT250INS-6M	250	6

SEMI-RIGID ALUMINIUM DUCTING



- Well suited to clothes dryers, range hoods, bathrooms and other general ventilation applications as it holds its shape when formed around obstacles.
- Temperature rating -70°C to +220°C.
- Complies with Australian/New Zealand Standards:
 - Fire and smoke control - AS/NZS 1668.1
 - 3 zero fire rating - AS/NZS 1530.3
 - Flexible ductwork - AS 4254

PART NO.	DUCT DIAMETER, MM	DUCT LENGTH, M	COMPRESSED, MM
DUCT100-3-SRIG	100	3	750
DUCT125-3-SRIG	125	3	750
DUCT150-3-SRIG	150	3	750
DUCT200-3-SRIG	200	3	750