	Disabled Refuge Systems	Disabled Refuge (Type B) Outstations	IP66 Rated Enclosure for EVC302GF or EVC302F Outstations
---	---	--	--

[◀ Back to Search results for "bf359/1" \(3 other results\)](#)



IP66 Rated Enclosure for EVC302GF or EVC302F Outstations

Part No. **BF359/1**

- An attractive IP66 rated enclosure designed for use with a SigTEL EVC302GF or EVC302F flush mounting disabled refuge controller.
- Includes a handle and mounting plate.
- Measures 200 W x 302 H x 123mm deep.
- Textured RAL 7035 (light grey) finish.
- Also compatible with C-TEC's EP210F remote status units.



Technical Specifications

Approvals/certifications	Enclosure is UL listed (Issue no. K-4256).
Compatibility	Can house an EVC302GF green or EVC302F stainless steel SigTEL outstation. Also compatible with EP210F Remote Status Units.
Product dimensions (mm)	200 W x 302 H x 123 D mm. Designed for surface mounting only.
Construction & finish	Sheet steel enclosure and door, dipcoat primed, powder-coated on the outside, textured paint (RAL 7035 grey). Also includes a green disabled refuge sticker.
IP Rating	IP66.
Weight	2.5kg (enclosure and mounting plate).


Dimensions & Mounting Information

Product dimensions:	200 W x 302 H x 123mm deep. Designed for flush mounting only.
----------------------------	---

Documentation

BF359/1 Instructions

DAU0359000 Rev 3

 Download (637.42k)

Accessories





Remote Status Unit, Flush



**Brushed Stainless Steel
Disabled Refuge Outstat...**



**Green Disabled Refuge
Outstation, flush**


4 other products in the same category:



**Green Disabled Refuge
Outstation, surface**



**Green Disabled Refuge
Outstation, flush**



Brushed Stainless Steel
Disabled Refuge...

Brushed Stainless Steel
Disabled Refuge...

CONTACT US



C-TEC , Challenge Way, Wigan, WN5 0LD, UK Opening times: 08:30 - 17:00 GMT.



+44 (0) 1942 322744



sales@c-tec.co.uk



Download map