



caresafe

NCATAK

CARESAFE ACCESSIBLE ALARM KIT V2

FEATURES & BENEFITS

- Call Accept functionality allows staff to send an intermittent call acknowledgment signal to confirm help is on the way
- 230V controller with a simple 12V system - Six core stranded security cable ideal for most installations
- All accessories c/w 25mm surface backboxes
- System can be easily expanded to include one additional caresafe overdoor light sounder (NCATAKOL)
- NCATAKPC Ceiling pull c/w a 3 metre cord & two triangular bangles for ease of use
- Relay Contacts
- Battery back-up facility (battery included)
- Designed to meet the criteria of care standards set out in part M building regulations and BS8300

KIT CONTENT

- Call controller c/w battery back up (NCATAKC)
- Reset point (NCATAKRP)
- Pull cord c/w 3 metre cord and triangle (NCATAKPC)
- Over door light and sounder (NCATAKOL)
- WC toilet sticker





care*safe*

NCATAK

CARESAFE ACCESSIBLE ALARM KIT V2

TECHNICAL SPECIFICATIONS

NCATAKC - Controller & PSU

- Supply Voltage: 230Va.c. 50/60Hz; Max. current: 200mA
- PSU Output: 12vDC current 350mA
- Relay contacts: Change over contacts, rated 30Vd.c. @ 3A
- Battery: A23 12 Volt Alkaline Battery
- Sounder: 66dB @ 1m
- IP Rating: IP54
- Dimensions: W87*H41*D87 (mm)
- Weight: 132g
- Operating Temp: 0~40°C

NCATAKPC - Ceiling Pull Unit

- Input: Voltage: 12vDC, Max. current: 10mA
- Pull cord: 3 metres cord length
- Indicator: Red reassurance LED, active in alarm
- Anti-Ligature break rating: 1.2kgf
- IP Rating: IP54
- Dimensions: W87*H41*D87 (mm)
- Weight: 117g
- Operating Temp: 0~40°C

NCATAKRP - Accessible Toilet Reset Point c/w Sounder

- Input: Voltage: 12vDC, Max. current: 20mA
- Indicator: Red reassurance LED, active in alarm.
- Sounder: 66dB
- Dimensions: W87*H41*D87 (mm)
- IP Rating: IP30
- Weight: 96g
- Operating Temp: 0~40°C

NCATAKOL - Overdoor Light c/w Sounder

- Input: Voltage: 12vDC, Max. current: 60mA
- Sounder @ 1m: 66dB
- IP Rating: IP30
- Dimensions: W87*H56*D87 (mm)
- Weight: 115g
- Operating Temp: 0~40°C

