

STEEL

- pvc coating - black

IP54

FSU-CP20B M20 thread

- 10 metres of galvanised steel with PVC coating
- Temperature range -15°C to +70°C
- Self extinguishing
- High mechanical strength
- Highly flexible

- 5 M20 fixed fittings
- 5 M20 swivel fittings
- 10 steel locknuts
- IP54

NYLON

- black

IP66

**FPAS-CP21B** M20 thread**FPAS-CP25B** M25 thread

- 10 metres of standard weight nylon PA6 FPAS21 or FPAS25
- Low fire hazard
- Halogen free
- Self extinguishing
- Low smoke and Low toxicity
- High flexibility and fatigue life
- High impact strength
- Oil and solvent resistant
- UV resistant

- Temperature range -40°C to +120°C
- 10 FPA fittings and locknuts FPA21-M20B or FPA25-M25B
- One part, fast fit
- Removable using a screwdriver
- High pull-off strength
- Anti-vibration
- IP66
- UV resistant

PVC SPIRAL

- black

IP54

FPC-CP20B M20 thread**FPC-CP25B** M25 thread

- 10 metres of spiral reinforced pvc FPC20 or FPC25
- Highly flexible
- Accepts torsional movement
- Self extinguishing
- UV resistant
- Temperature range -5°C to +70°C

- 10 MPC fittings and locknuts
- IP65
- UV resistant
- Smooth bore

NYLON

- black

IP66

NEW

FPYE-CP20B M20 thread**FPYE-CP25B** M25 thread

- 10 metres of light weight nylon PA6 FPAL20 or FPAL25
- Flexible
- Halogen free
- Self extinguishing
- Temperature range -40°C to +120°C

- 10 Flexlok fittings and locknuts FLK20-M20B or FLK25-M25B
- IP66
- One part, fast fit

POLYPROPYLENE

- black or grey

IP66

NEW

FPP-CP20B M20 thread**FPP-CP25B** M25 thread

- 10 metres of polypropylene FPP20 or FPP25
- Temperature range -20°C to +90°C
- Self extinguishing
- To specify grey change B to a G eg: FPP-CP20G

- 10 Flexlok (PP) fittings and locknuts FLK20-M20-PP or FLK25-M25-PP
- IP66
- One part, fast fit

