

T8 Luxline Plus Special Length Tri-Phosphor

201070

- T8 Luxline Plus Special Length Tri-Phosphor
- High luminous efficacy
- Operates on conventional and electronic ballasts



Performance

Lamp Power	30W
Exit Lumen	2230lm
CCT	6500K
CRI	80
Beam Angle	360°
Warranty	1 Years


Physical

Dimensions	L895 x W26 x H26 mm
------------	---------------------

Electrical

Voltage	96V
---------	-----

Line Drawings



	A	B	B	C	D
	max	min	max	max	nom
15W	437.4	442.1	444.5	451.6	26
25W 28*	691.4	696.1	698.5	705.6	26
25W 30*	742.2	746.9	749.3	756.4	26
25W 33*	818.4	823.1	825.5	832.6	26
30W	894.6	899.3	901.7	908.8	26
36W	970.0	974.1	977.1	984.2	26
38W	1050.0	1051.7	1054.1	1061.2	26
70W	1763.8	1768.5	1770.9	1778.0	26

*Rated LED design life where stated is based upon application of Pierlite's operating and maintenance guidelines; see pierlite.com.au. Actual product life may vary dependent upon frequency of maintenance and product application. Due to continual product improvement, information is subject to change without notification. Gerard Lighting Pty Ltd standard Terms and Conditions apply