



TL-D Standard Colours

TL-D 15W/33-640 1SL/9

Low-pressure mercury discharge lamps with a tubular 26 mm envelope

Warnings and Safety


- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Mechanical and Housing	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Bulb Shape	T8
Life to 50% Failures (Nom)	13,000 h	Net Weight (Piece)	0.077 kg
Light Technical		Approval and Application	
Color Code	33-640	Mercury (Hg) Content (Nom)	8.0 mg
Luminous Flux	830 lm	Product Data	
Color Designation	Cool White (CW)	Order product name	TL-D 15W/33-640 1SL/9
Correlated Color Temperature (Nom)	4100 K	Full product name	TL-D 15W/33-640 1SL/9
Color rendering index (CRI)	63	Full product code	871150070277700
Operating and Electrical		Local code description	TLD15W33
Power Consumption	15.0 W	Order code	928024803347
Lamp Current (Nom)	0.310 A	Material Nr. (12NC)	928024803347
Voltage (Nom)	51 V	Local order code	TLD15W33
Controls and Dimming		Numerator - Quantity Per Pack	1
Dimmable	Yes	EAN/UPC - Product/Case	8711500702777
		Numerator - Packs per outer box	9
		EAN/UPC - Case	8711500287441


TL-D Standard Colours

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL-D 15W/33-640 1SL/9	28 mm	437.4 mm	444.5 mm	442.1 mm	451.6 mm

Photometric data




Spectral Power Distribution Colour - TL-D 15W/33-640 1SL/9

Lifetime




Life expectancy diagram - 3 hour cycle



Life expectancy diagram - 12 hour cycle

TL-D Standard Colours

Lifetime



Lumen Maintenance Diagram - TL-D 15W/33-640 1SL/9

