Product data sheet
Characteristics

GGBL13FCUWPW
Lisse - Fuse Carrier - 13 A - white moulded with White Interior



Main

Range	Lisse
Aesthetic name	White moulded
Product or component-type	Fuse carrier
Device presentation	Complete product
Colour tint	White interior White moulded cover plate
Quantity per set	Set of 1

Complementary

Pilot light	Without LED
Number of gangs	1 gang
Material	Urea (carbamide)
Device mounting	Wall mounted
Fixing mode	By screws
Rated current	13 A, 250 V AC
Connections - terminals	Screw terminals
Type of packing	Carton
Width	28 mm
Height	59 mm
Depth	24 mm
Product weight	0.027 kg

Environment

Standards	BS 5733
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1809 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Product Life Status : Commercialised

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.