Product data sheet Characteristics

GU3210DBPC

Ultimate Flat plate - switched socket - 2P - 1 gang - chrome



Main

Aesthetic name	Flat plate	
Product or component type	Switched socket	
Rated current	13 A at 230 V AC 50 Hz	
Fixing mode	By screws M3.5 x 30 mm	
Colour tint	Chrome	

Complementary

Complementary	
Device presentation	Complete product
Outlet poles configuration	2P
Outlet standard description	3 pins
Outlet standard	British
Actuator	Rocker
Number of gangs	1 gang
Earth circuit	Standard earth
Pilot light	Without neon indicator
Device mounting	Wall mounted
Connections - terminals	Screw terminal
Material	Steel
Quantity per set	Set of 1
Height	88 Mm
Width	88 Mm
Depth	30 Mm
Socket number	2

Environment

IP degree of protection	IP20	
Standards	BS 1363	

Packing Units

0.144 Kg	
4.100 Cm	
10.100 Cm	
10.300 Cm	
	4.100 Cm 10.100 Cm

Offer Sustainability

REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	☑ China RoHS Declaration	

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : Commercialised