



Main

Range	Ultimate
Device application	Power supply
Aesthetic name	Flat plate
Product or component type	Switched socket
Rated current	13 A at 230 V AC 50 Hz
Fixing mode	By screws M3.5 x 30 mm
Colour tint	Chrome

Complementary

Device presentation	Complete product
Outlet poles configuration	1P
Outlet standard description	3 pins
Outlet standard	British
Actuator	Rocker
Number of gangs	2 gangs
Earth circuit	Standard earth
Pilot light	Without neon indicator
Device mounting	Wall mounted
Connections - terminals	Screw terminal
Material	Stainless steel
Quantity per set	Set of 1
Height	88 Mm
Width	148 Mm
Depth	30 Mm
Socket number	2
Mounting mode	Horizontal

Environment

IP degree of protection	IP20
Standards	BS

Packing Units

Package 1 Weight	0.246 Kg
Package 1 Height	4.100 Cm
Package 1 width	10.100 Cm
Package 1 Length	16.300 Cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	Commercialised
-----------------------	----------------