Product data sheet
Characteristics

GU4421BPC
Ultimate Screwless flat plate - 2-pole switch - 2 gangs - polished chrome



Main

Range of product	Ultimate
Range	Ultimate
Aesthetic name	Screwless flat plate
Product or component type	Switch
Switch function	2-pole
Rated current	50 A at 230 V AC

Complementary

Connections - terminals	Screw terminals
Quantity per set	Set of 1
Number of gangs	2 gangs
Pilot light	Red neon indicator
Height	148 Mm
Width	88 Mm

Environment

Standards	BS EN 60669-1
IP degree of protection	IP20

Packing Units

Package 1 Weight	0.320 Kg
Package 1 Height	4.200 Cm
Package 1 width	9.000 Cm
Package 1 Length	16.200 Cm

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty	18 months

Product Life Status :	Commercialised