Product data sheet
Characteristics

GU5400BPC
Ultimate Screwless flat plate - unswitched fused connection - chrome

Main

Range	Ultimate
Device application	Protection
Aesthetic name	Screwless flat plate
Product or component type	Unswitched fused connection
Switch function	-
Colour tint	Black Chrome

Complementary

Pilot light	Without neon indicator
Number of gangs	1 gang
Material	Steel
Mounting support	Wall mounted
Fixing mode	By screws
Rated current	13 A at 230 V AC
Connections - terminals	Screw terminals
Quantity per set	Set of 1
Height	88 Mm
Width	88 Mm
Depth	23 Mm
Fuse type	Blade type

Environment

IP degree of protection	IP20
Standards	BS 1363

Packing Units

Package 1 Weight	0.179 Kg
Package 1 Height	4.200 Cm
Package 1 width	9.000 Cm
Package 1 Length	10.300 Cm

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months

Product Life Status :	Commercialised

Schneider Electric