

Before Use:

- Read all instructions
- All ladders have a maximum load of 150Kg
- Keep the ladder clean - remove any paint, oil or dirt
- Inspect the ladder before first use - check operation of all parts and ensure it is safe to use at the start of each day
- Do not use a damaged ladder
- Before using the ladder at work, a risk assessment should be carried out
- For professional users, regular periodic inspection is required

Positioning the Ladder:

- Ladders should not be positioned on slippery surfaces (for example ice, shiny surfaces or on spillages) unless additional effective measures are taken to prevent the ladder slipping
- When positioning the ladder take into account risk of collision from people, vehicles, doors and windows. Secure doors (not fire exits) and windows where possible in the work area
- Ladder should be positioned on an even level and unmoveable base with rungs or treads level and fully opened
- Ladder should only be used on its feet in the upright position
- Identify any electrical risks in the work area, such as overhead lines or other exposed electrical equipment
- Locking devices, if fitted, should be fully secured before use
- Ladder should never be repositioned from above

Using the Ladder:

- Do not exceed the maximum total load for the type of ladder
- Do not overreach
- Avoid work that imposes a sideways load on standing ladders, such as side-on drilling through solid materials (e.g. brick and concrete)
- Wear suitable footwear when climbing a ladder
- Face the ladder when ascending and descending
- Do not use standing ladders for access to another level
- Use non-conductive ladders for unavoidable live electrical work
- Do not use the ladder as a bridge
- Equipment carried while using a ladder should be light and easy to handle
- Do not use the ladder outside in adverse weather conditions, such as strong wind
- Children should not use the ladder as a toy or without supervision
- Ladders should only be used for light work of short duration with regular breaks
- Care should be taken when opening and closing the legs

Storage:

The important considerations when storing a ladder (not in use) include the following:

- To avoid more rapid deterioration ensure the ladder is stored away from areas of dampness, excessive heat, or exposure to the elements
- The ladder should be stored in a position which helps it to remain straight (e.g. hung by the stiles on proper ladder brackets or laid on a flat clutter free surface)
- The ladder should be stored where it cannot be damaged by vehicles, heavy objects, or contaminants
- Ensure the ladder is stored where it cannot cause a trip hazard or an obstruction
- Ensure the ladder is secured against unauthorised usage (e.g. by children or criminals)

Repair:

These ladders are not repairable, if damaged they should be disposed of.

Maintenance:

Refer to the 'Before Use' section of the instructions.

GUARANTEE
Your GreenBrook LADP is
guaranteed for 1 year from the
date of purchase.
This is in addition to your statutory rights.

PLEASE KEEP THESE INSTRUCTIONS SAFE FOR FUTURE REFERENCE