



GSE IN-ROOF SYSTEM™

BIPV SYSTEM FOR ALL PHOTOVOLTAIC MODULES

RANGE
2022

QUICK, AESTHETIC, LIGHTWEIGHT,
WATERPROOF AND COST-COMPETITIVE



MADE IN FRANCE

www.gseintegration.com

The GSE **IN-ROOF SYSTEM** range is expanding

MODULES UP TO 400 Wp 2012 AND 2020 RANGE

MODULES UP TO 600 Wp 2022 RANGE

PORTRAIT:



19 available references*
Module length: 1535 to 1780 mm
Module width: 803 to 1055 mm



21 available references*
Module length: 1554 to 1740 mm
Module width: 768 to 1120 mm

* Detailed list available on our website: www.gseintegration.com

LANDSCAPE:



21 available references*
Module length: 1610 to 1990 mm
Module width: 990 to 1160 mm

UP TO 450 Wp:

UP TO 600 Wp:

Coming early 2023,
new portrait frames for XL PV modules!

BENEFITS

- Economic: the most competitive system for roof renovations and new constructions
- Easy to install: 10 to 16 panels installed in 6 hours
- Flexible: achieve any desired configuration type (U-Shape, pyramid, etc...)
- Lightweight and space-saving: 58 frames per pallet

PRODUCT CERTIFIED IN MANY COUNTRIES

- Resistance to fire
- Completely waterproof: ensures complete watertightness of the PV system and the roof
- Optimal ventilation
- Impact resistance
- Very important mechanical resistance:
 - Downward pressure: 5400 Pa (IEC 61215)
 - Upward pressure: up to 5500 Pa (NF EN 12179)
 - Eurocode design values: Snow: 1800 Pa, Wind: 1700 Pa

TECHNICAL SPECIFICATIONS



All types
Roof covering



Slope
12° to 60°



Weight
2.8 to 3.7 kg/m²



Temperature range
-30°C to 100°C



Material
PP - Aluminium - Stainless steel
(100% Recyclable)

NEW: EVEN EASIER TO INSTALL

Integration of all new PV
modules generations.
Until 150 mm of height
adjustment possible

Pre-drilled fixing
points



Simplified clamps
installation: position
indication

Optimized cable passed
for all junction boxes

LIABILITY INSURANCE TRADING AND PRODUCT **CHUBB®**

CERTIFICATIONS

-       
 - Universel kit: ALPES CONTROLE: ETN A27T2109 Many modules approved (list available on our website)
 - Avis Technique n°21/16-57_V5 7
GSE Intégration "Toit Solaire" V. TS-2, A-2 et TN-1
 - BBA: MCS 012 certifiée no. "MCS BBA 0156" -
compatible with more than 30 PV panels - maximum wind load: 2.71 kN/m²
 - System Performance Assessment (certification in progress)
 - DIBt: Allgemeine bauaufsichtlichen Zulassung no. Z-14.4-817 (certification in progress)

FIRE TESTS EXPOSURE

- BRoof T1   
- BRoof T2    
- BRoof T3 
- BRoof T4 

GSE

Intégration

OUR TIME-SAVING TOOLS

CALCULATOR

Allows you to find out which GSE IN-ROOF SYSTEM plate is compatible with your panel and to determine the overall size of the final PV field in just a few clicks.

CONFIGURATOR

Allows you to establish a list of materials needed for your GSE IN-ROOF SYSTEM installation.

INSTALLATION MANUALS AND GUIDES

Find these tools here:



A DEDICATED CONTACT PERSON FOR EACH REQUEST

A battening plan or a technical question? technical.support@gseintegration.fr

Any other request? contact@gseintegration.fr