



ADA940T

RCBO 1P+N 6kA C-40A 30mA A Class

Technical characteristics

Architecture

Neutral position	right
Number of protected poles	1
Number of poles	2 P
Type of pole	1P+N
Fixing mode	DIN rail type O (symmetrical)
Curve	C

Configuration

Number of modules	2
-------------------	---

Connectivity

Top connection alignment for modular devices	Aligned terminal
Bottom connection alignment for modular devices	Aligned terminal

Main electrical features

Rated operational voltage U_e	230 - 240 V~
Type of supply voltage	AC

Voltage

Dielectric strength value of power frequency	2 kV
Rated insulation voltage	500 V
Max operating voltage	240 V
Rated impulse withstand voltage	4 kV

Electric current

Rated residual operating current	30 mA
Rated current	40 A
Withstand not tripping on 8-20 μ s wave	250 A
Breaking and opening capacity	4500 A
min/maxi threshold value of the AC thermal operation	1,13 / 1,45 I_n
Magnetic regulating current	5 / 10 I_n

Electric current / temperature

Rating current -25°C	46,9 A
Rating current -20°C	46,3 A
Rating current -15°C	45,6 A
Rating current -10°C	45 A
Rating current -5°C	44,4 A
Rating current 0°C	43,8 A
Rating current 30°C	40 A

Rating current 35°C	39,4 A
Rating current 40°C	38,8 A
Rating current 45°C	38,2 A
Rating current 50°C	37,5 A
Rating current 55°C	36,9 A
Rating current 60°C	36,2 A
Rating current 70°C	27,2 A
Current correction factors	
Correction factor of rating current for 2 devices placed side-by-side	1
Correction factor of rating current for 3 devices placed side-by-side	0,95
Correction factor of rating current for 4 and 5 devices placed side-by-side	0,9
Correction factor of rating current for 6 devices placed side-by-side	0,85
Dimensions	
Depth of installed product	68 mm
Height of installed product	83 mm
Width of installed product	35 mm
Frequency	
Frequency	50 Hz
Power	
Total power loss under IN	11,1 W
Power loss per pole at In	6,2 W
Endurance	
Electric endurance in number of cycles	2000
Number of mechanical operations	1000
Installation, mounting	
Type of top connection for modular devices	with screw
Tightening torque	2,1Nm
Type of top rail clip for modular devices	NA
Type of bottom rail clip for modular devices	plastic
Type of Bottom Connection for modular devices	Blconnect + bypass
Top removability for modular devices	
Bottom removability for modular devices	
Suitable for flush-mounting	
Connection	
Connection cross-section at output with screw, for flexible conductor	1 / 16 mm ²
Connection cross-section at output with screw, for massive conductor	1 / 25 mm ²
Connection cross-section for rigid conductor, upstream terminals with screws	1 / 25 mm ²
Connection cross-section of the access with screws, with flexible conductor	1 / 16 mm ²
Cage clamp position	in line
Downstream cage clamp delivery status	opened
Upstream cage clamp delivery status	opened

Connection cross-section of input and output with screws, for massive conductors	1 / 25 mm ²
Connection cross section of access and exit with screws, for flexible conductor	1 / 16 mm ²
Cable	
Length of conductors used for the heating test (m) according to product standard	1 m
Conductor cross-section used for heating test(mm ²) according to product standard	10 mm ²
Equipment	
Can be accessorized	
With transparent product label holder	
Standards	
Standard text	IEC 61009-1 AS/NZS 61009-1
European directive WEEE	not concerned
Safety	
Protection index IP	IP2X
Residual current type	A
Use conditions	
Operating temperature	-25...40 °C
Degree of pollution according to IEC 60664 / IEC 60947-2	2
Class of energy limitation I ² t	3
Altitude	2000 m
Air humidity protection	for all climates
Storage/transport temperature	-25...70 °C
temperatur	
Temperature of calibration	30 °C
Ambient air temperature during heating test according to the product standard	23,7 °C
Max. admissible temperature on accessible parts (intended to be touched)	61,1 °C
Max. admissible temperature on accessible parts (manual operating means)	49,1 °C
Max. admissible temperature on access. parts (not touched for normal operation)	82,6 °C
Max. admissible temperature on terminals	75,8 °C
Temp.-rise limits for access. parts (toggle) according to product standard	25 K
Temp.-rise limits for access. parts (not touched) according to product standard	60 K
Temp.rise limits for access. parts (to be touched) according to product standard	40 K
Temperature-rise limits for terminals according to the product standard	65 K
Temperature-rise measured on accessible parts at In (manual operating means)	9,1 K
Temperature-rise measured on access. parts at In (not touched normal operation)	42,6 K
Temperature-rise measured on accessible parts at In (intended to be touched)	21,1 K
Temperature-rise measured on terminals at In	35,8 K