



ADC225B

RCBO 1M 1P 10kA C-25A 30mA A

Technical properties

Architecture

| | |
|--------------|----|
| Type of pole | 1P |
| Curve | C |

Electric current

| | |
|-------------------------------------------------------|---------------|
| Rated current | 25 A |
| Rated residual operating current I _{dn} | 30 mA |
| Rated current -25°C | 33,11 A |
| Rated current at -20°C | 32,38 A |
| Rated current -15°C | 31,64 A |
| Rated current -10°C | 30,90 A |
| Rated current -5°C | 30,16 A |
| Rated current at 0°C | 29,43 A |
| Rated current 5°C | 28,69 A |
| Rated current 10°C | 27,95 A |
| Rated current 15°C | 27,21 A |
| Rated current at 20°C | 26,48 A |
| Rated current 25°C | 25,74 A |
| Rated current 30°C | 25 A |
| Rated current 35°C | 24,18 A |
| Rated current at 40°C | 23,35 A |
| Rated current at 50°C | 21,70 A |
| Rated current 55°C | 20,88 A |
| Rated current 60°C | 20,05 A |
| Min./max. threshold value of the AC thermal operation | 1,13 - 1,45 A |

Safety

| | |
|-------------------------------|------|
| Residual current type | A |
| Ingress Protection (IP) class | IP20 |

Main electrical attributes

| | |
|-----------------------------------------------------------------------------------|-------|
| Rated short-circuit breaking capacity I _{cn} AC according to IEC 60898-1 | 10 kA |
|-----------------------------------------------------------------------------------|-------|

Voltage

| | |
|--------------------------------------------------|-------------|
| Rated insulation voltage U _i | 250 V |
| Rated impulse withstand voltage U _{imp} | 4000 V |
| Rated operational voltage U _e | 230 - 240 V |

Power

| | |
|---------------------------|--------|
| Total power loss under IN | 8,40 W |
|---------------------------|--------|

Frequency

| | |
|-----------|------------|
| Frequency | 50 - 60 Hz |
|-----------|------------|

Use conditions

| | |
|---------------------------------------------|-------------|
| Altitude | 2000 m |
| Class of energy limitation I ² t | 3 |
| Operating temperature | -5 - 40 °C |
| Storage/transport temperature | -40 - 70 °C |

Endurance

| | |
|----------------------------------------|-------|
| Electric endurance in number of cycles | 2000 |
| Number of mechanical operations | 10000 |

Connection

| | |
|------------------------------------------------------------------------|------------------------|
| Cross-section of input with screws, for flexible conductors | 1 - 10 mm ² |
| Cross-section of input with screws, for massive conductors | 1 - 16 mm ² |
| Cross-section of input and output with screws, for flexible conductors | 1 - 16 mm ² |
| Cross-section of input and output with screws, for massive conductors | 1 - 25 mm ² |

Installation, mounting

| | |
|-----------------------------------------------|----------------|
| Type of top connection for modular devices | Screw terminal |
| Type of bottom connection for modular devices | biconnect |

Capacity

| | |
|-------------------|---|
| Number of modules | 1 |
|-------------------|---|

Dimensions

| | |
|--------|----------|
| Height | 115 mm |
| Width | 17,80 mm |
| Depth | 70 mm |

Compatibility

| | |
|-----------------------|-----|
| Suitable for DIN Rail | Yes |
|-----------------------|-----|