



ADC245B

RCBO 1M 1P 10kA C-45A 30mA A

Technical properties

Architecture

Type of pole	1P
Curve	C

Electric current

Rated current	45 A
Rated residual operating current I _{dn}	30 mA
Rated current -25°C	55,45 A
Rated current at -20°C	54,50 A
Rated current -15°C	53,55 A
Rated current -10°C	52,60 A
Rated current -5°C	51,65 A
Rated current at 0°C	50,70 A
Rated current 5°C	49,75 A
Rated current 10°C	48,80 A
Rated current 15°C	47,85 A
Rated current at 20°C	46,90 A
Rated current 25°C	45,95 A
Rated current 30°C	45 A
Rated current 35°C	44,50 A
Rated current at 40°C	44 A
Rated current at 50°C	43 A
Rated current 55°C	42,50 A
Rated current 60°C	42 A
Min./max. threshold value of the AC thermal operation	1,13 - 1,45 A

Safety

Residual current type	A
Ingress Protection (IP) class	IP20

Main electrical attributes

Rated short-circuit breaking capacity I _{cn} AC according to IEC 60898-1	10 kA
---	-------

Voltage

Rated insulation voltage U _i	250 V
Rated impulse withstand voltage U _{imp}	4000 V
Rated operational voltage U _e	230 - 240 V

Power

Total power loss under IN	12,90 W
---------------------------	---------

Frequency

Frequency	50 - 60 Hz
-----------	------------

Use conditions

Altitude	2000 m
Class of energy limitation I ² t	3
Operating temperature	-5 - 40 °C
Storage/transport temperature	-40 - 70 °C

Endurance

Electric endurance in number of cycles	2000
Number of mechanical operations	10000

Connection

Cross-section of input with screws, for flexible conductors	1 - 10 mm ²
Cross-section of input with screws, for massive conductors	1 - 16 mm ²
Cross-section of input and output with screws, for flexible conductors	1 - 16 mm ²
Cross-section of input and output with screws, for massive conductors	1 - 25 mm ²

Installation, mounting

Type of top connection for modular devices	Screw terminal
Type of bottom connection for modular devices	biconnect

Capacity

Number of modules	1
-------------------	---

Dimensions

Height	115 mm
Width	17,80 mm
Depth	70 mm

Compatibility

Suitable for DIN Rail	Yes
-----------------------	-----