



ADC250B

**RCBO 1M 1P 10kA C-50A 30mA A**

**Technical properties**

**Architecture**

Type of pole	1P
Curve	C

**Electric current**

Rated current	50 A
Rated residual operating current I <sub>dn</sub>	30 mA
Rated current -25°C	63,89 A
Rated current at -20°C	62,63 A
Rated current -15°C	61,36 A
Rated current -10°C	60,10 A
Rated current -5°C	58,84 A
Rated current at 0°C	57,58 A
Rated current 5°C	56,31 A
Rated current 10°C	55,05 A
Rated current 15°C	53,79 A
Rated current at 20°C	52,53 A
Rated current 25°C	51,26 A
Rated current 30°C	50 A
Rated current 35°C	49,38 A
Rated current at 40°C	48,75 A
Rated current at 50°C	47,50 A
Rated current 55°C	46,88 A
Rated current 60°C	46,25 A
Min./max. threshold value of the AC thermal operation	1,13 - 1,45 A

**Safety**

Residual current type	A
Ingress Protection (IP) class	IP20

**Main electrical attributes**

Rated short-circuit breaking capacity I <sub>cn</sub> AC according to IEC 60898-1	10 kA
-----------------------------------------------------------------------------------	-------

**Voltage**

Rated insulation voltage U <sub>i</sub>	250 V
Rated impulse withstand voltage U <sub>imp</sub>	4000 V
Rated operational voltage U <sub>e</sub>	230 - 240 V

### Power

Total power loss under IN	10,80 W
---------------------------	---------

### Frequency

Frequency	50 - 60 Hz
-----------	------------

### Use conditions

Altitude	2000 m
Class of energy limitation I <sup>2</sup> t	3
Operating temperature	-5 - 40 °C
Storage/transport temperature	-40 - 70 °C

### Endurance

Electric endurance in number of cycles	2000
Number of mechanical operations	10000

### Connection

Cross-section of input with screws, for flexible conductors	1 - 10 mm <sup>2</sup>
Cross-section of input with screws, for massive conductors	1 - 16 mm <sup>2</sup>
Cross-section of input and output with screws, for flexible conductors	1 - 16 mm <sup>2</sup>
Cross-section of input and output with screws, for massive conductors	1 - 25 mm <sup>2</sup>

### Installation, mounting

Type of top connection for modular devices	Screw terminal
Type of bottom connection for modular devices	biconnect

### Capacity

Number of modules	1
-------------------	---

### Dimensions

Height	115 mm
Width	17,80 mm
Depth	70 mm

### Compatibility

Suitable for DIN Rail	Yes
-----------------------	-----