



HMF380T

## MCB 3P 10kA C-80A 4.5M

### Technical characteristics

#### Architecture

Number of poles	3 P
Type of pole	3 P
Curve	C

#### Main electrical features

Rated operational voltage Ue	415 V
Frequency	50/60 Hz
Rated current	80 A
Type of supply voltage	AC

#### Voltage

Rated insulation voltage	500 V
Rated impulse withstand voltage	6000 V

#### Electric current

Rated short circuit breaking capacity I <sub>cn</sub> under 230V AC according IEC60898-1	10 kA
---	-------

#### Electric current / temperature

Rating current 30°C	80 A
---------------------	------

#### Dimensions

Depth of installed product	70 mm
Height of installed product	90 mm
Width of installed product	80 mm

#### Power

Total power loss under I <sub>N</sub>	20,32 W
---------------------------------------	---------

#### Endurance

Electric endurance in number of cycles	4000
Number of mechanical operations	20000

#### Capacity

Number of modules	4,5
-------------------	-----

#### Installation, mounting

Tightening torque	3,5 to 5Nm
-------------------	------------

#### Connection

Connection cross-sect. flexible conductor	50mm <sup>2</sup>
Connection cross-sect. rigid cable	70mm <sup>2</sup>
Type of connection	terminal with tightening compensation system

#### Standards

Standard text	EN 60898-1 IEC 60947-2 AS/NZS 60898-1
European directive WEEE	concerned

