



MSN225



**MCB 2P 6kA C-25A 2M**

**Technical characteristics**

**Architecture**

Neutral position	without neutral
Number of poles	2 P
Type of pole	2 P
Fixing mode	DIN rail type O (symmetrical)
Curve	C

**Functions**

Concurrently switching N-neutral

**Configuration**

Number of modules	2
-------------------	---

**Connectivity**

Top connection alignment for modular devices	Aligned terminal
Bottom connection alignment for modular devices	Aligned terminal

**Main electrical features**

Rated operational voltage $U_e$	415 V
Type of supply voltage	AC

**Voltage**

Rated insulation voltage	500 V
Max operating voltage	415 V
Rated impulse withstand voltage	4000 V

**Electric current**

Rated current	25 A
Rated service breaking capacity $I_{cs}$ AC according IEC 60898-1	6 kA
min/maxi threshold value of the AC thermal operation	1,13 / 1,45 $I_n$
Magnetic regulating current	5 / 10 $I_n$
Rated short circuit breaking capacity $I_{cn}$ under 400V AC according IEC60898-1	6 kA
Rated short circuit breaking capacity $I_{cn}$ under 415V AC according IEC 60898-1	6 kA

**Electric current / temperature**

Rating current -25°C	33,35 A
Rating current -20°C	32,58 A
Rating current -15°C	31,81 A
Rating current -10°C	31,01 A
Rating current -5°C	30,27 A
Rating current 0°C	29,51 A

Rating current 30°C	25 A
Rating current 35°C	24,13 A
Rating current 40°C	23,36 A
Rating current 45°C	22,59 A
Rating current 50°C	21,75 A
Rating current 55°C	21,05 A
Rating current 60°C	20,28 A
Rating current 65°C	19,51 A
Rating current 70°C	18,75 A
<b>Current correction factors</b>	
Correction factor of rating current for 2 devices placed side-by-side	1
Correction factor of rating current for 3 devices placed side-by-side	0,95
Correction factor of rating current for 4 and 5 devices placed side-by-side	0,9
Correction factor of rating current for 6 devices placed side-by-side	0,85
<b>Dimensions</b>	
Depth of installed product	70 mm
Height of installed product	83 mm
Width of installed product	35 mm
<b>Frequency</b>	
Frequency	50 to 60 Hz
<b>Power</b>	
Maximum power loss per pole according to the product standard	4,5 W
Total power loss under IN	6 W
Power loss per pole at In	3,05 W
<b>Endurance</b>	
Electric endurance in number of cycles	4000
Number of mechanical operations	20000
<b>Installation, mounting</b>	
Type of top connection for modular devices	with screw
Tightening torque	2,8Nm
Type of bottom rail clip for modular devices	plastic
Type of Bottom Connection for modular devices	Blconnect
Top removability for modular devices	
Bottom removability for modular devices	
<b>Connection</b>	
Connection cross-section at output with screw, for flexible conductor	1 / 25 mm <sup>2</sup>
Connection cross-section at output with screw, for massive conductor	1 / 35 mm <sup>2</sup>
Connection cross-section for rigid conductor, upstream terminals with screws	1 / 35 mm <sup>2</sup>
Connection cross-section of the access with screws, with flexible conductor	1 / 25 mm <sup>2</sup>
Downstream cage clamp delivery status	opened
Upstream cage clamp delivery status	opened

Subject to technical modifications

---

**Equipment**

---

Can be accessorized

---

With transparent product label holder

---

**Standards**

---

Standard text	IEC 60898-1 AS/NZS 60898-1
European directive WEEE	not concerned

---

**Safety**

---

Protection index IP	IP20
---------------------	------

---

**Use conditions**

---

Operating temperature	-25...70 °C
-----------------------	-------------

---

Degree of pollution according to IEC 60664 / IEC 60947-2	2
---	---

---

Class of energy limitation I <sup>2</sup> t	3
---	---

---

Altitude	2000 m
----------	--------

---

Storage/transport temperature	-25...80 °C
-------------------------------	-------------

---

**temperatur**

---

Temperature of calibration	30 °C
----------------------------	-------

---