



NDN363A



MCB 3P 10kA D-63A 3M

Technical characteristics

Architecture

| | |
|---------------------------|-----------------|
| Neutral position | without neutral |
| Number of protected poles | 3 |
| Number of poles | 3 P |
| Type of pole | 3 P |
| Curve | D |

Functions

Concurrently switching N-neutral

Configuration

| | |
|-------------------|---|
| Number of modules | 3 |
|-------------------|---|

Connectivity

| | |
|---|------------------|
| Top connection alignment for modular devices | Aligned terminal |
| Bottom connection alignment for modular devices | Aligned terminal |

Main electrical features

| | |
|--|-------|
| Rated short circuit breaking capacity I_{cn} AC according IEC60898-1 | 10 kA |
| Rated operational voltage U_e | 415 V |
| Type of supply voltage | AC |

Voltage

| | |
|--|--------|
| Rated insulation voltage | 500 V |
| Max operating voltage | 440 V |
| Rated impulse withstand voltage | 6000 V |
| Minimum threshold voltage (U_e min) | 12 V |

Electric current

| | |
|---|-------------------|
| Rated current | 63 A |
| Rated service breaking capacity I_{cs} AC according IEC 60898-1 | 7,5 kA |
| min/maxi threshold value of the AC thermal operation | 1,13 / 1,45 I_n |
| Magnetic regulating current | 10 / 14,4 I_n |
| min/maxi threshold value of the DC magnetic operation | 15 / 30 I_n |
| min/maxi threshold value of the DC thermal operation | 1,13 / 1,45 I_n |
| Rating current -10°C according to IEC 60947 | 83,72 A |
| Rating current -15°C according to IEC 60947 | 85,22 A |
| Rating current -20°C according to IEC 60947 | 86,7 A |

| | |
|---|---------|
| Rating current -25°C according to IEC 60947 | 88,15 A |
| Rating current -5°C according to IEC 60947 | 82,2 A |
| Rating current 0°C according to IEC 60947 | 80,64 A |
| Rating current 30°C according to IEC 60947 | 70,59 A |
| Rating current 35°C according to IEC 60947 | 68,77 A |
| Rating current 40°C according to IEC 60947 | 66,9 A |
| Rating current 45°C according to IEC 60947 | 64,98 A |
| Rating current 50°C according to IEC 60947 | 63 A |
| Rating current 55°C according to IEC 60947 | 60,26 A |
| Rating current 60°C according to IEC 60947 | 57,38 A |
| Rating current 65°C according to IEC 60947 | 54,35 A |
| Rating current 70°C according to IEC 60947 | 51,14 A |
| Rated short circuit breaking capacity Icn under 230V AC according IEC60898-1 | 10 kA |
| Rated short circuit breaking capacity Icn under 400V AC according IEC60898-1 | 10 kA |
| Rated ultimate short-circuit breaking capacity Icu under 230V AC IEC 60947-2 | 30 kA |
| Rated ultimate short-circuit breaking capacity Icu under 240V AC IEC 60947-2 | 30 kA |
| Rated ultimate short-circuit breaking capacity Icu under 400V AC IEC 60947-2 | 15 kA |
| Rated ultimate short-circuit breaking capacity Icu under 415V AC IEC 60947-2 | 15 kA |
| Rated short circuit breaking capacity Icn under 240V AC according IEC 60898-1 | 10 kA |
| Rated short circuit breaking capacity Icn under 415V AC according IEC 60898-1 | 10 kA |
| Rated ultimate short-circuit breaking capacity Icu under 220V AC IEC 60947-2 | 30 kA |
| Rated ultimate short-circuit breaking capacity Icu under 380V AC IEC 60947-2 | 15 kA |
| Electric current / temperature | |
| Rating current -25°C | 78,67 A |
| Rating current -20°C | 77,38 A |
| Rating current -15°C | 76,06 A |
| Rating current -10°C | 74,72 A |
| Rating current -5°C | 73,36 A |
| Rating current 0°C | 71,97 A |
| Rating current 30°C | 63 A |
| Rating current 35°C | 60,96 A |
| Rating current 40°C | 58,86 A |
| Rating current 45°C | 56,68 A |
| Rating current 50°C | 54,4 A |
| Rating current 55°C | 52,03 A |
| Rating current 60°C | 49,55 A |
| Rating current 65°C | 46,94 A |
| Rating current 70°C | 44,17 A |
| Current correction factors | |

| | |
|--|------------------------|
| Correction factor of rating current for 2 devices placed side-by-side | 1 |
| Correction factor of rating current for 3 devices placed side-by-side | 0,95 |
| Correction factor of rating current for 4 and 5 devices placed side-by-side | 0,9 |
| Correction factor of rating current for 6 devices placed side-by-side | 0,85 |
| Correction factor of magnetic tripping with 100 Hz | 1,1 |
| Correction factor of magnetic tripping with 200 Hz | 1,2 |
| Correction factor of magnetic tripping with 400 Hz | 1,5 |
| Correction factor of magnetic tripping with 60 Hz | 1,1 |
| Dimensions | |
| Depth of installed product | 70 mm |
| Height of installed product | 83 mm |
| Width of installed product | 52,5 mm |
| Frequency | |
| Frequency | 50 to 60 Hz |
| Power | |
| Maximum power loss per pole according to the product standard | 13 W |
| Total power loss under IN | 19,9 W |
| Power loss per pole at In | 7,12 W |
| Endurance | |
| Electric endurance in number of cycles | 4000 |
| Number of mechanical operations | 20000 |
| Installation, mounting | |
| Type of top connection for modular devices | with screw |
| Tightening torque | 2,8Nm |
| Type of top rail clip for modular devices | NA |
| Type of bottom rail clip for modular devices | plastic |
| Type of Bottom Connection for modular devices | Blconnect |
| Top removability for modular devices | |
| Bottom removability for modular devices | |
| Suitable for flush-mounting | |
| Connection | |
| Connection cross-section at output with screw, for flexible conductor | 1 / 25 mm ² |
| Connection cross-section at output with screw, for massive conductor | 1 / 35 mm ² |
| Connection cross-section for rigid conductor, upstream terminals with screws | 1 / 35 mm ² |
| Connection cross-section of the access with screws, with flexible conductor | 1 / 25 mm ² |
| Downstream cage clamp delivery status | opened |
| Upstream cage clamp delivery status | opened |
| Equipment | |

Can be accessorized

Standards

| | |
|-------------------------|------------------------------|
| Standard text | EN 60898-1 AS/NZS 60898-1 |
| European directive WEEE | concerned |

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

Use conditions

| | |
|-----------------------|-------------|
| Operating temperature | -25...70 °C |
|-----------------------|-------------|

| | |
|---|---|
| Degree of pollution according to IEC 60664 / IEC 60947-2 | 2 |
|---|---|

| | |
|----------|--------|
| Altitude | 2000 m |
|----------|--------|

| | |
|-------------------------------|-------------|
| Storage/transport temperature | -25...80 °C |
|-------------------------------|-------------|

temperatur

| | |
|----------------------------|-------|
| Temperature of calibration | 30 °C |
|----------------------------|-------|
