



VD102NT



Sm.distr.,VD/IC²,surface,1row,2M,IP30,no terminals,AUS,without door

Technical properties

Voltage

| | |
|-----------------|-------------|
| Nominal voltage | 400 - 400 V |
|-----------------|-------------|

Installation, mounting

| | |
|----------------------------|----|
| Suitable for outdoor usage | No |
|----------------------------|----|

| | |
|-------------|------------------|
| Mounting on | Surface mounting |
|-------------|------------------|

Electric current

| | |
|---------------|------|
| Rated current | 63 A |
|---------------|------|

Equipment

| | |
|-----------------|---|
| Number of rails | 1 |
|-----------------|---|

| | |
|----------------|---|
| Number of rows | 1 |
|----------------|---|

| | |
|----------------------------|---|
| Number of section in width | 1 |
|----------------------------|---|

| | |
|-----------|----|
| With lock | No |
|-----------|----|

| | |
|----------------------------|----|
| Has neutral terminal block | No |
|----------------------------|----|

| | |
|-----------------------------|----|
| Has earthing terminal block | No |
|-----------------------------|----|

| | |
|--------------------|----|
| Has mounting plate | No |
|--------------------|----|

Capacity

| | |
|-------------------|---|
| Number of modules | 2 |
|-------------------|---|

Functions

| | |
|---------------------|-----|
| With conduit inlets | Yes |
|---------------------|-----|

Dimensions

| | |
|--------|-----------|
| Height | 163,50 mm |
|--------|-----------|

| | |
|-------|----------|
| Width | 45,50 mm |
|-------|----------|

| | |
|-------|-------|
| Depth | 71 mm |
|-------|-------|

| | |
|-----------------------|---|
| Number of width units | 2 |
|-----------------------|---|

Cover, door

| | |
|-------------------------|---|
| Number of cabinet doors | 0 |
|-------------------------|---|

| | |
|-----------------|---|
| Number of locks | 0 |
|-----------------|---|

Materials

| | |
|----------|---------|
| Material | Plastic |
|----------|---------|

| | |
|----------|------|
| RAL code | 9010 |
|----------|------|

| | |
|--------|------------|
| Colour | Pure white |
|--------|------------|

| | |
|-----------------------|----|
| Ultraviolet-resistant | No |
|-----------------------|----|

Safety

| | |
|-------------------------------|--------------------|
| Protection class | Isolation class II |
| Impact resistance IK | IK07 |
| Ingress Protection (IP) class | IP30 |
| Locking type | Without lock |
| Glow wire test | 750 °C |