



VF312PT



Small distributor,golf,flush,3row,36M,IP40,MS-terminal,Australia,N+PE,white door

Technical properties

Functions

With a pipe-in lead	Yes
---------------------	-----

Configuration

Number of modules	36
-------------------	----

Main electrical features

Nominal voltage	400 V
-----------------	-------

Electric current

Rated current	80 A
---------------	------

Dimensions

Insertion depth	72 mm
Depth of installed product	97.5 mm
Internal depth	97.5 mm
Height of installed product	543 mm
Installation height	507 mm
Width of installed product	352 mm
Width in division units	12
Built-in height	507 mm
Built-in width	318 mm

Cover, door

Identification of protection index	40
Interlockable	No
Number of keylock of the door	0
Cover type	Closed (plain)
Door locking	without
Door leave	single
Cover type	Door
Transparent cover or door	No

Materials

Colour	white
RAL colour	RAL 9010 - Pure white
Material	plastic
Type of surface treatment	untreated

Installation, mounting

Suitable for outdoor use

No

Settings

Enclosure type

Distributor empty cabinet

Equipment

Number of rows

3

Quantity of section in width

1

Quantity of rails

3

Can be accessorized

Yes

Number of openings for flange plates

0

Extension possible

Yes

Earthing terminal block

Yes

Neutral terminal block

Yes

Signal passing door

Yes

Safety

IK protection code against mechanical impacts

IK07

Protection class

isol.class II

REACH conform

No

RoHS conform

Yes

Halogen free

No

Use conditions

Operating temperature

-25...40 °C