



VF412PT



Small distributor,golf,flush,4row,IP40,48M,MS-terminal,Australia,N+PE,white door

Technical properties

Functions

With a pipe-in lead	Yes
---------------------	-----

Configuration

Number of modules	48
-------------------	----

Main electrical features

Nominal voltage	400 V
-----------------	-------

Electric current

Rated current	80 A
---------------	------

Dimensions

Insertion depth	72 mm
-----------------	-------

Depth of installed product	97.5 mm
----------------------------	---------

Internal depth	97.5 mm
----------------	---------

Height of installed product	688 mm
-----------------------------	--------

Installation height	652 mm
---------------------	--------

Width of installed product	352 mm
----------------------------	--------

Width in division units	12
-------------------------	----

Built-in height	652 mm
-----------------	--------

Built-in width	318 mm
----------------	--------

Cover, door

Identification of protection index	40
------------------------------------	----

Interlockable	No
---------------	----

Number of keylock of the door	0
-------------------------------	---

Cover type	Closed (plain)
------------	----------------

Door locking	without
--------------	---------

Door leave	single
------------	--------

Cover type	Door
------------	------

Transparent cover or door	No
---------------------------	----

Materials

Colour	white
--------	-------

RAL colour	RAL 9010 - Pure white
------------	-----------------------

Material	plastic
----------	---------

Type of surface treatment	untreated
---------------------------	-----------

Installation, mounting

Suitable for outdoor use

No

Settings

Enclosure type

Distributor empty cabinet

Equipment

Number of rows

4

Quantity of section in width

1

Quantity of rails

4

Can be accessorized

Yes

Number of openings for flange plates

0

Extension possible

Yes

Earthing terminal block

Yes

Neutral terminal block

Yes

Signal passing door

Yes

Safety

IK protection code against mechanical impacts

IK07

Protection class

isol.class II

REACH conform

No

RoHS conform

Yes

Halogen free

No

Use conditions

Operating temperature

-25...40 °C