



## Weatherproof 2G 16A switch

WBWS216

### Architecture

|                      |        |
|----------------------|--------|
| Type of control unit | rocker |
|----------------------|--------|

### Configuration

|                             |
|-----------------------------|
| - 2 way, with loop terminal |
|-----------------------------|

### Controls and indicators

|                   |   |
|-------------------|---|
| Number of buttons | 2 |
|-------------------|---|

### Main electrical features

|                 |       |
|-----------------|-------|
| Nominal voltage | 250 V |
|-----------------|-------|

### Electric current

|               |      |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

### Materials

|                    |                                   |
|--------------------|-----------------------------------|
| Colour             | light grey                        |
| Colour             | light grey                        |
| Material           | Polycarbonate (PC), UV-stabilised |
| Surface appearance | glossy                            |

### Dimensions

|        |       |
|--------|-------|
| Height | 85 mm |
| Width  | 85 mm |

### Installation, mounting

|                   |                     |
|-------------------|---------------------|
| Mounting type     | surface-mounted     |
| Installation mode | for screw fastening |

### Connection

|                    |                  |
|--------------------|------------------|
| Type of connection | Screw connection |
|--------------------|------------------|

**Safety**

|                     |      |
|---------------------|------|
| Protection index IP | IP66 |
|---------------------|------|

**Identification**

|                  |                   |
|------------------|-------------------|
| Main design line | Weather protected |
|------------------|-------------------|