

making connections beautifully

| Wiring Accessories • Circuit Protection • Lighting Control & Multi-room Audio 86R24WH-W Sheer Satin Chrome 4 gang 10AX 2 Way Rocker White/White | | | | | |
|---|---|--|------------|--------|--|
| | | | Item Image | Wiring | Dimensions |
| | | | | | Hemilton SHEER R24 2 Way Rocker |
| | Image: second | | | | |
| Primary Range | Sheer | | | | |
| Insert Type | 2 Way Rocker | | | | |
| Plate Finish | Sheer Satin Chrome | | | | |
| Insert Colour | White | | | | |
| Dimensions (Nominal) | Double: Height = 86.0mm Width = 146.0mm Depth = 1.5mm | | | | |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = N/A | | | | |
| Minimum Wall Box Depth | 25mm | | | | |
| Switched Poles | Single | | | | |
| Current Rating | 10AX | | | | |
| | 220/250V AC | | | | |
| Voltage Maximum Load | 10 Amp inductive | | | | |
| | 50Hz | | | | |
| Mains Frequency IP Rating | IP2XD | | | | |
| Contact Gap Minimum | 3mm | | | | |
| Terminal Capacity 1 | | | | | |
| Terminal Capacity 2 | 5 x 1mm2 4 x 1.5mm2 | | | | |
| | 4 x 1.5mm2 1 x 2.5mm2 | | | | |
| Terminal Capacity 3 | 1 x 2.5mm2 1 x 4mm2 Multi-strand | | | | |
| Terminal Capacity 4 | | | | | |
| Terminal Capacity 5 | 1 x 6mm2 | | | | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | | | | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | | | | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | | | | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | | | | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | | | | |
| Product Class 1 | Must be earthed | | | | |
| Ambient Operating Temperature | -5° to +40°C | | | | |
| Recommended Location | Internal Use Only | | | | |
| Maximum Installation Altitude | 2000m | | | | |
| Standard/Approval | BS EN 60669-1 | | | | |
| Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. | Trade Mark No. 2296586 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. | | | |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 31 March 2017 04:15 PM E&OE | | | |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Of E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in | ad, Brislington, Bristol, BS4 5NZ fice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84 | Listed in Trimble Product Product Selector DISFPLUE | | | |