

# BLADE G2

**BLADE06-TRI**  
SAP CODE: 2002306


## Modern, low profile design

BLADE G2 is a sleek and modern LED batten, ideal when low profile and high output is required. This aesthetically pleasing batten delivers cost savings without compromising light output.

### APPLICATIONS

Laundry, Entrance, Garage, Boardroom / Meeting Rooms, Function Areas, Education Facilities, Storage Rooms, Kitchen / Food Prep

### DIMENSION DIAGRAMS



### KEY INFORMATION

Power	20 W
Lumen Output	2000 / 2200 / 2000 lm
Mounting Type	Surface Mount
Dimming Type	Non-Dimmable
Fascia Colour	White RAL9016
IP Rating	IP20
IK Rating	Not applicable
Operating Ambient Temp.	-25 to 45°C
Connection Type	PA12 Terminals
Driver	Integral
Warranty	5 yrs

### PHOTOMETRIC

Efficacy	up to 117 lm/W
CCT	4000 / 4700 / 5700 K
CRI	> 80
SDCM	< 3
UGR	> 25
Beam Angle	120°
Flicker-Free	No
Lifespan	>50,000hrs @ Ta 25°C (L70)

### ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

### OTHERS

Body Material	Polycarbonate
Diffuser Material	Polycarbonate (Opal)
Cable Entry	Rear
Rebate Scheme Approvals	IPART; REPS;
HACCP Approval	Yes
Weight	0.9 kg
Dimensions	620 x 100 x 30 mm