



OVOLO**OVL230R-DIM**

SAP CODE: 2002313

**Impressive, classic
and all-purpose.**

The versatile OVOLO series combines practical functionality with impressive features. This ultra lightweight downlight comes in a range of sizes which allows for direct replacement of compact fluorescent and metal halide products.

**PHOTOMETRIC
DIAGRAM**

Unit: cd
C0/180 99.6deg
C90/270 99.7deg

Photometric diagram shown is for
4000K output.

MECHANICAL

IP Rating	IP63 (front face only)
IC Rating	DO NOT COVER
Dimensions (LxW)	Ø230mm
Dimensions (H)	75mm
Weight	0.56 kg
Mounting Type	Recessed
Cutout	Ø195mm
Body Material	SPCC/PC/Silicone
Diffuser Material	Polycarbonate Diffuser
Product Colour	White RAL9016 + PANTONE Cool Gray 11C
Operating Ambient Temperature	-20 to 45°C
Connection Type	0.9m Flex & Plug

ELECTRICAL

Wattage	23 / 30W
Lumen Output	2148 / 2479 / 2332 lm (23W) 2823 / 3273 / 3073 lm (30W)
Efficacy	Up to 120 lm/W
Input Voltage	220-240Vac, 50/60Hz
Surge Protection	Overload / Short Circuit
Power Factor	>0.9
Electrical Classification	Class 2
Driver	Remote
Dimming Method	Phase Cut (Trailing Edge) Dimmable
Smart	KASTA Compatible
Lifespan	>50,000hrs @ Ta 25°C (L70)

OPTICAL

CCT	3000 / 4000 / 5700K
CRI	> 80
UGR	< 32
Beam Angle	100°
SDCM	< 7

OTHER

Warranty	5 yrs
Government Scheme Approval	N/A
HACCP Approved	No