models to fit wider and taller openings



features

- reliable and easy to install with restyled enclosure
- automatic safety cut-out
- fan-only setting for cool air circulation
- adjustable mounting bracket on 3.0, 4.5 and 6.0kW
- improved performance on 3.0, 4.5, 6.0 and 9.0kW compact models

3.0 KW
HSAC3000X
HSAC3000SS

4.5 KW
HSAC4500X

6.0 KW
HSAC6000X

9.0 KW
HSAC9000CX
HSAC9000XN

12.0 KW
HSAC12000X

2
YEAR SERVICE WARRANTY

Designed for installation above doorways to reduce heat loss from buildings, the range includes PROFILE styling on the 3, 4.5, 6 and 9kW Compact models – with improved performance – a Compact 9kW model and the stylish 3kW stainless steel model. The 6kW unit is designed to be mounted at normal height to heat wider doorways. The 9kW and 12kW models are for extra tall or wide double doorways and are supplied as standard with a remote switching controller for power selection and air circulation.

The stylish HSAC3000SS 3kW stainless-steel model is great for a designer look.





Remote switching is standard on 9kW and 12kW models. The optional HSRCU1 kit is available for HS3000X, 4500X and 6000X

specification

HSAC	3000X	3000SS	4500X	6000X	9000CX	9000XN	12000X
RATING kW	3.0	3.0	4.5	6.0	9.0	9.0	12.0
PHASE	1	1	1	1	3/1	3/1	3/1
NOISE dB @1m	46	59	46	49	52	52	52
WEIGHT kG	5	5.5	5	7	9	26	26
DIMENSIONS mm h	211	210	211	211	211	300	300
w	622	634	622	1035	1035	1300	1300
d	115	175/67	115	115	115	235	235

Self re-setting cut-out. CE

