


Part number

PEW 12565 SI



Flush-mounting plug, PLUSO series, 3 poles + N + PE, 6 h (red), 125 A, 380 ÷ 415 V

Product description

Product type	Plug Flush-mounting
Series	PEW...SI, PLUSO
Connection type	Screw terminal connection
N. of poles	3 poles + N + 
Clock position	6

Technical data

Current	125 A
Voltage	380 ÷ 415 V
IP degree of protection	IP67

Further technical details

Weight	1.318,00 g
Operating temperature range (min, max)	-25°C ... +40°C

Material properties

Colour	RAL 7035 grey, RAL 3000 red
---------------	-----------------------------

Approvals / Standards

Reference standard	EN 60309-1 and -2
---------------------------	-------------------

General ordering information

EAN13 code	8015747070621
-------------------	---------------

Packaging Information

Packaging length	245,00 mm
Packaging height	165,00 mm
Packaging width	215,00 mm
Packaging weight	3,20 kg
Packaging volume	8,69 dm ³

Packaging description	Carton box
------------------------------	------------

Packaging quantity	2 Pcs
---------------------------	-------

Packaging EAN code	8015747070638
---------------------------	---------------

Part number

PEW 12565 SI



Notes

Dimensions shown in mm are not binding and may be changed without notice.

-
- Compliant with EN 60309-1 and -2
 - Enclosure, insert and locking ring in insulating, thermoplastic, self-extinguishing material
 - Flange with anti-ageing gasket
 - PE...SI types (IP44), RAL 7035 grey enclosure, plug mouth colour coded according to the operating voltage
 - PEW...SI (IP67) types, RAL 7035 grey enclosure, locking ring with gasket colour coded according to the operating voltage
 - Terminals with retained screws
 - 63A, 125A: with pilot contact
 - Nickel-plated contacts, available on request for 16A and 32A (standard on 63A and 125A). For the code of products with nickel-plated contacts (socket holes, plug pins), add "N" to the pre-code of the corresponding standard product code; for example: PE becomes PEN and PEW becomes PEWN.
 - IP44 and IP67 degrees of protection (EN 60529)
-