

Part number

TM 12564 SP



Interlocked switched socket-outlet, TM series,
3 poles + PE, 6 h (red), 125 A, 380 ÷ 415 V,
without fuse-carrier, with base box

Product description

Product type	Interlocked switched socket-outlet
Series	TM..SP/KSP
N. of poles	3 poles + 
Clock position	6
Specification	Without fuse-carrier With base box

Technical data

Current	125 A
Voltage	380 ÷ 415 V
IP degree of protection	IP66/IP67
Further technical details	
Weight	9,11 g
Operating temperature range (min, max)	-25°C ... +40°C
UL 94 flammability rating	V-0 (insert), V-2 (enclosure)
IK rating (impact degree of protection)	IK10

Material properties

Colour	RAL 7012 grey, RAL 3000 red
---------------	-----------------------------

General ordering information

EAN13 code	8015747251136
-------------------	---------------

Packaging Information

Packaging length	630,00 mm
Packaging height	300,00 mm
Packaging width	280,00 mm
Packaging weight	10,64 kg
Packaging volume	52,92 dm ³
Packaging description	Carton box
Packaging quantity	1 Pcs
Packaging EAN code	8015747257626

Part number

TM 12564 SP



Notes

Dimensions shown in mm are not binding and may be changed without notice.
