Part number

TM 1643 IR



Interlocked switched socket-outlet, TM series, 2 poles + PE, 4 h (yellow), 16 A, 100 ÷ 130 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, with base box


Product description	
Product type	Interlocked switched socket-outlet
Series	TM..IR/KIR
N. of poles	2 poles + ⏚
Clock position	4
Size	115 x 450 x 18 mm
Specification	With compartment for modular units, 4,5 DIN-rail modules EN 60715 With base box
Technical data	
Current	16 A
Voltage	100 ÷ 130 V
IP degree of protection	IP66/IP67
Further technical details	
Weight	1.310,00 g
Operating temperature range (min, max)	-25°C ... +40°C
UL 94 flammability rating	V-2
IK rating (impact degree of protection)	IK10


Material properties	
Colour	RAL 7012 grey, RAL 1021 yellow
Approvals / Standards	
Reference standard	EN 60309-1 and -2
General ordering information	
EAN13 code	8015747089531
Packaging Information	
Packaging weight	12,35 kg
Packaging volume	52,36 dm³
Packaging description	Carton box
Packaging quantity	9 Pcs
Packaging EAN code	8015747089548
Sub-packaging weight	1,37 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747089555

Part number

TM 1643 IR

Catalogue drawings





	A	B
2P+⏚	133	276
3P+⏚	135	276
3P+N+⏚	140	277

Notes

Dimensions shown in mm are not binding and may be changed without notice.