

Part number

TM 3243KIR



Interlocked switched socket-outlet, TM series, 2 poles + PE, 4 h (yellow), 32 A, 100 ÷ 130 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, with base box

Product description

Product type	Interlocked switched socket-outlet
Series	TM..IR/KIR
N. of poles	2 poles + 
Clock position	4
Size	115 x 450 x 18 mm
Specification	With compartment for modular units, 4,5 DIN-rail modules EN 60715 With base box

Technical data

Current	32 A
Voltage	100 ÷ 130 V
IP degree of protection	IP66/IP67

Further technical details

Weight	1.370,00 g
Operating temperature range (min, max)	-25°C ... +40°C
UL 94 flammability rating	V-2
IK rating (impact degree of protection)	IK10

Material properties

Colour	RAL 7012 grey, RAL 1021 yellow
---------------	--------------------------------

Approvals / Standards

Reference standard	EN 60309-1 and -2
---------------------------	-------------------

General ordering information

EAN13 code	8015747126427
-------------------	---------------

Packaging Information


Packaging weight	12,33 kg
Packaging volume	55,44 dm ³
Packaging description	Carton box
Packaging quantity	9 Pcs
Packaging EAN code	8015747098786
Sub-packaging weight	1,37 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747099325

Part number

TM 3243KIR



Catalogue drawings



Notes

Dimensions shown in mm are not binding and may be changed without notice.