

Part number

TM 3264KIR



Interlocked switched socket-outlet, TM series, 3 poles + PE, 6 h (red), 32 A, 380 ÷ 415 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, with base box

Product description

Product type	Interlocked switched socket-outlet
Series	TM..IR/KIR
N. of poles	3 poles + 
Clock position	6
Size	115 x 450 x 18 mm
Specification	With compartment for modular units, 4,5 DIN-rail modules EN 60715 With base box

Technical data

Current	32 A
Voltage	380 ÷ 415 V
IP degree of protection	IP66/IP67

Further technical details

Weight	1.410,00 g
Operating temperature range (min, max)	-25°C ... +40°C
UL 94 flammability rating	V-2
IK rating (impact degree of protection)	IK10

Material properties

Colour	RAL 7012 grey, RAL 3000 red
---------------	-----------------------------

Approvals / Standards

Reference standard	EN 60309-1 and -2
---------------------------	-------------------

General ordering information

EAN13 code	8015747126076
-------------------	---------------

Packaging Information


Packaging length	385,00 mm
Packaging height	320,00 mm
Packaging width	485,00 mm
Packaging weight	12,69 kg
Packaging volume	59,75 dm ³
Packaging description	Carton box
Packaging quantity	9 Pcs
Packaging EAN code	8015747126809
Sub-packaging weight	1,41 kg
Sub-packaging description	Carton tray
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747126816

Part number

TM 3264KIR



Catalogue drawings



Notes

Dimensions shown in mm are not binding and may be changed without notice.